

SECOND RE-ESTABLISHMENT

GCDB 600200

Section corner common to Sections 25, 26, 35 and 36, Township 36 South, Range 1 East.

Found the Southwest White Oak bearing tree (now 5") intact; also found a snag of the Southeast Black Oak bearing tree (now 10"), opened same and found scribing; also found a fir stump to the Northwest and a Black Oak stump hole to the Northeast with a "BT" chip from same.

For corner, set a 1"x36" galvanized iron pipe 32" in the ground with a 2½" bronze cap stamped:

T36S, R1E	
Section cor.	
26	25
----- C.S.	
35	36
1964	

From which:

- The above mentioned 5" White Oak bears South 50° West, 13.9 feet;
- The 10" Black Oak snag bears South 15° East, 10.6 feet;
- The fir stump bears North 67° West, 6.6 feet.

From said pipe corner, I establish the following new witness trees:

- An 8" Fir scribed "CS-BT" bears South 35° West, 24.8 feet to the face of the lower blaze;
- A 14" Yellow Pine scribed "CS-BT" bears South 53° East, 30.1 feet to the face of the lower blaze;
- A 10" Fir scribed "CS-BT" bears North 14° East, 26.9 feet to the face of the upper blaze;
- A 10" White Oak scribed "CS-BT" bears North 65° West, 57.1 feet to the face of the upper blaze.

April 23, 1964
L. D. Pinkham
Lloyd Hart
Vic Gardner, present

Approved by:
Mark E. Boyden, County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600200

Section corner common to Sections 25, 26, 35 and 36, Township 36 South, Range 1 East, W.M.

Found projecting 8 ins. in a mound of stones, the 1 ins. diam. galvanized iron pipe with 2½ ins. diam. bronze cap marked:

T36S R1E	
26	25
CS	
35	36
1964	

As described on first re-establishment, in 1964.

Original bearing tree marked by Ives and Hyde in 1854 found:

- White Oak, now 6 ins. diam. with rotted lower face, brs. Record: S50°W, 13.9 feet to estimated original lower face.

Bearing trees marked on first re-establishment found:

- Fir snag, 10 ins. diam. with double healed blazes, brs. N13½°E, 26.9 feet to upper face. Record; N14°E.
- Yellow Pine, now 15 ins. diam. with double healed blazes, brs. S52½°E, 30.1 feet to estimated lower face. Record; S53°E. Re-measured 30.8 feet to center of tree at lower blaze.
- Fir snag, 9 ins diam., with double healed blazes, brs. S34½°W, 24.8 feet to lower face.
- White Oak, now 10 ins. diam. with double healed blazes, brs. N65½°W, 57.1 feet to estimated upper face. Record; N65°W. Re-measured 57.46 feet to center of tree at lower blaze.

Mk new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Oak, 12 ins. diam., brs. S69°W, 22.38 feet.
- Douglas Fir, 7 ins. diam., brs. N46½°W, 30.35 feet.

Corner lies in a wooded area, on a 17% North slope, 7.8 feet West of a north-South fence.

November 13, 1986
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 17½°
P. -310