

## FIRST RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Sections 1 and 2, Township 36 South, Range 1 East, W.M.  $V = 20\frac{1}{2}^\circ$

From the following evidence and at the location noted below, I set a 1 x 36 ins. G.I. pipe 28 ins. in the ground with a  $2\frac{1}{2}$  ins. bronze disc marked:

T36S R1E  
¼S  
2 | 1  
Jackson County 1974

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A hollow White Oak snag containing chain notch and scribe marks in rotted lower face, bears N  $11\frac{1}{2}^\circ$  E, 40.92 feet to scribed face. Record, N  $14\frac{1}{2}^\circ$  E, 40.92 feet.
- A White Oak, 11 ins. diam., containing scribed "S" in opened upper face, bears record, West, 43.56 feet to scribed face.

I mound stones around corner marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 12 ins. diam., bears S  $16^\circ$  E, 24.95 feet.
- A double Black Oak, 6 ins. diam., bears N  $74^\circ$  W, 51.10 feet.

Corner lies 1.5 feet West of North-South fence line.

March 20, 1974

B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor