

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 1 ONLY
GCDB 640700**

The north quarter corner of Section 1, Township 36 South, Range 1 East, W.M. $V = 20^\circ$

From the following evidence and at the location described below I set a 1 x 36 ins. G.I. pipe 10 ins. in the ground with a 2½ ins. bronze disc marked:

T35S
¼S
—
1
T36S R1E
Jackson County 1974

Original BTs marked by Ives and Hyde in 1854 feet as follows:

- W White Oak, 12 ins. diam., containing scribe "4/S" in exposed and weathered upper face, bears record, N13°E, 52.14 feet to scribed face.
- The base of a down and rotted Black Oak, about 15 ins. diam., with reverse impression of scribed "BT" bears record, S37°W, 43.56 feet.

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 11 ins. diam., bears N48°E, 32.9 feet.
- A White Oak, 6 ins. diam., bears S7½°E, 13.47 feet.
- The South ¼ of Sections 36 bears S86½°E, 66.0 feet.
- A N-S fence line bears East, 46.0 feet.

May 9, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor