

FIRST RE-ESTABLISHMENT

GCDB 700340

Quarter Section corner on the Range line common to Section 24, Township 36 South, Range 1 East and Section 19, Township 36 South, Range 2 East, W.M.

Found 1¼ " x? iron pipe to mark the corner;

From which

- The original BT with the BT scribe legible checks the Government official Record
- Scribe an 8" White Oak C.S.-BT which bears N48¾°W, 70.5 feet.
- Scribe a 6" White Oak C.S.-BT which bears S39½°E, 34.8 feet.

October 12, 1936
C. Z. Boyden, Deputy County Surveyor

D. J. Clifford, Chainman
C. I. Bourne, Chainman
C. W. Klinge, (present)

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700340

Quarter corner common to Secton 19, Township 36 South, Range 2 East and Section 24, Township 36 South, Range 1 East, W.M.

Found projecting 3 ins. in mound of stone, the 1 ¼ ins. diam. galvanized iron pipe, reported on first re-establishment, in 1936. In the top of found pipe, set a 2½ ins. diam. brass cap marked:

T36S
¼S
R1E R2E
24 | 19
C.S.
1986

Bearing trees marked on first re-establishment, found and measured to center of trees at lower blaze:

- White Oak, 11 ins. diam., containing scribed "CS" in exposed upper face, brs. S39½°E, 34.8 feet.
- White Oak, 10 ins. diam., with healed blazes, brs. N48¾°W, 70.95 feet. Record; 70.5 feet.

Mk a new tree "CS" "BT":

- Ponderosa Pine, 8 ins. diam., brs. N32°E, 43.24 feet to center of tree at lower blaze.

Corner lies 18 ins. West of North-South fence line and an estimated 100 feet North of middle of irrigation ditch, c. N60°W.

May 16, 1986
R. Frost
T. Newcomb
Witness: V. Gardener

Edward McGinty
County Surveyor

V = 19½°

P.-126