


FIRST RE-ESTABLISHMENT

GCDB 700400

Corner common to Sections 13 and 24, Township 36 South, Range 1 East and Sections 18 and 19, Township 36 South, Range 2 East.

Set a 1"x36" galvanized iron pipe 36" in the ground with a 2½" brass cap stamped:



From which the original White Oak, now 20" in diameter, bears North 13° West, 130.7 feet.

Marked the following new trees:

- A 24" Black Oak scribed CS-BT bears South 73½° West, 87.4 feet to the face of the upper blaze;
- A 7" White Oak scribed CS-BT bears North 30° West, 36.5 feet to the face of the upper blaze;
- A 14" twin White Oak scribed CS-BT bears North 4½° East, 106.0 feet to the face of the upper blaze.
- (fence corner bears Northerly 5 feet)

June 27, 1967
 L. D. Pinkham, Deputy County Surveyor
 G. Kaiser


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700400

Corner common to Sections 13 and 24, Township 36 South, Range 1 East and Sections 18 and 19, Township 36 South, Range 2 East.

Found 2½ ins. diam. brass disc on a 1½ ins. diam. galvanized iron pipe per First Re-establishment, dated 1967, exposed 6 ins. Cap marked:



Bearing trees recorded on First Re-establishment found and measured to side center at lower blaze:

- White Oak , original bearing tree, 20 ins. diam., with opened blaze and rotted face, bears N12°48'56"W, 131.12 ft. Record N13°W, 130.7 ft.
- White Oak, easterly trunk now 14 ins. diam., with double healed blazes, bears N29° 20'56"W, 37.09 ft.; Record N30°W, 36.5 ft. to face of upper blaze.
- White Oak, southerly trunk now 18 ins. diam., with double healed blazes, bears N04°50'22"E, 107.02 ft.; Record N04°30'E, 106.0 ft. to face of upper blaze.

Set new references as follows;

- 5/8 x 24 ins. rebar with a 2 ins. diam. aluminum cap marked "Jackson County Surveyor" 2 ins. deep, bears N31°27'04"E, 81.24 ft. Located approx. 40 ft. southerly of a toe of a slope, and approx. 40 ft. easterly of an East-West-South fenceline intersection.
- Mag spike, flush with ground, bears N09°21'39"W, 67.33 ft. Located approx. 70 ft. northerly of an East-West-South fence intersection.

Corner is located at the intersection of East-West-South fencelines.

June 27, 2018
J. Hall
T. Kaiser

Scott Fein
Jackson County Surveyor