

FIRST RE-ESTABLISHMENT

GCDB 700440

Re-establishment Quarter corner on Range Line between Section 13, Township 36 South, Range 1 East, and Section 18, Township 36 South, Range 2 East, W.M.

Found the original pine BT to Southeast plainly scribed.

From which set a 1" x 20" iron pipe, 5" below the surface of the county road for the corner

From which:

- A 14" Black Oak scribed CS-BT bears N19½°W, 159.9 feet.
- A 10" Black Oak scribed CS-BT bears N86½°E, 125.0 feet.

July 6, 1948
C. Z. Boyden
L. D. Pinkham

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700440

Quarter corner common to Section 18, Township 36 South, Range 2 East and Section 13, Township 36 South, Range 1 East, W.M.

Found 4 ins. below surface of Salt Creek Road, the 1 ins. diam. iron pipe reported set on first re-establishment, page 9, in 1948. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S
¼S
13 | 18
R1E | R2E
C.S.
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Sawed Pine stump, 17 ins. diam. with scribe marks including "1/ s" visible in exposed upper face, brs. S58°E, 32.85 feet to said face. Record; S56°E, 33.00 feet

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of tree at lower blaze:

- Black Oak, now 14 ins. diam. brs. N87°E, 125.40 feet. Record; N86½°E, 125.0 feet.
- Black Oak, now 19 ins. diam., brs. Record: N19½°W, 160.45 feet. Record distance; 159.9 feet.

The center of a 16 ins. diam. Pine corner post to fences bearing Northeast, Southwest and North, with an old location poster attached, brs. N¼°E, 32.7 feet.

Corner lies 8.0 feet South of the middle of Salt Creek Road (gravel), course N75°E-S75°W.

March 10, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18½°
P. - 88

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 700440

Quarter corner common to Section 13, Township 36 South, Range 1 East and Section 18, Township 36 South, Range 2 East, W.M.

Found at the corner position, 3 ins. deep, and the 2½ ins. diam. brass cap set on Second Re-establishment in 1988, marked:

T36S
¼S
13 • 18
R1E | R2E
C.S.
1988

Bearing trees recorded on First Re-establishment in 1948, found with healed double blazes and measured to center of trees at lower blaze:

- Black Oak 14 ins. diam. brs. N86½°E, 125.4 feet. Record; N87°E.
- Black Oak 19 ins. diam. brs. Record: N19½°W, 160.45 feet.

Take new references, 1 x 24 ins. rebars set flush with 1½ ins. diam. bronze caps marked:

JACKSON COUNTY

SURVEYOR

Bear:

- S 25°00'40" W, 21.90 feet.
- N 69°43'55" W, 50.20 feet.

Corner lies approximately 8 feet south of center of Salt Creek Road and S ¼° W, 32.7 feet of center of 16 ins. diam. fence corner post with location poster attached.

January 30, 2008

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 19
Nikon Total Station


SEE NEXT PAGE FOR CORNER REPORT

CORNER REPORT

GCDB 700440

Quarter corner common to Section 13, Township 36 South, Range 1 East and Section 18, Township 36 South, Range 2 East, W.M.

Found at the corner position, 3 ins. deep, the 2½ ins. diameter brass cap set on Second Re-establishment in 1988, marked:



From which;

Bearing tree marked on the First Re-establishment in 1948 and recorded on the Third Re-establishment, dated 2008, found;

- Black Oak 19 ins. diam., with healed double blazes brs. 2008 record N19½°W, 160.45 ft.

Found references set on Third Re-Establishment, being 1½ ins. diam. bronze caps marked:



- Bears record, S25°00'40"W, 21.90 feet.
- Bears record, N69°43'55"W, 50.20 feet.

Tree recorded as 14 ins. diam. Black Oak on previous re-estab was found dead and down with marker tag still attached. Did not remeasure.

Corner lies approximately 8 feet south of center of Salt Creek Road and S ¼° W, 32.7 feet of center of 16 ins. diam. fence corner post with location poster attached.

April 19, 2017
B. Paull

Scott D. Fein
Jackson County Surveyor

P. -