

FIRST RE-ESTABLISHMENT

GCDB 700500

Corner to Sections 7 and 18, on township line Township 36 South, Range 2 East, W.M. and 12 and 13, Township 36 South, Range 1 East, W.M.

- Found original BT to SE intact which bears S.40°E., 73.3 feet.
- The BT to NW down. Scribe visible.
- Remains of BT stump to NE checks okay.

Set 2" x 36" galvanized pipe for corner, 12" in the ground in mound of stone 3 feet square at base.

- Scribe 5" white oak C.S.-BT which bears S. 09°40'W., 114.5 feet.
- Scribe a 10" white oak C.S.-BT which bears N. 11°30' E., 45.6 feet.
- Scribe a 5" white oak C.S.-BT which bears N. 18°30' W., 39.9 feet.

October 26, 1928
Boyden, Deputy County Surveyor
O. H. Tice, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 700500

Section corner common to Sections 7 and 18, Township 36 South, Range 2 East and Sections 12 and 13, Township 36 South, Range 1 East, W.M.

Found projecting 24 ins., the 2 ins. diam. iron pipe, set on First re-establishment, page 2, in 1928. In the top of said pipe, set a 2½ ins. diam. brass cap marked:

| | |
|-------|-----|
| T36S | |
| R1E | R2E |
| 12 | 7 |
| ----- | |
| 13 | 18 |
| C.S. | |
| 1985 | |

The single remaining original bearing tree recorded by Ives and Hyde in 1854,

- A White Oak, now 21 ins. diam. with healed blazes, brs. S38°E, 73.0 feet to center of tree at lower blaze. Record; S40°E, 73.26 feet.

Bearing trees marked on First re-establishment, found with healed blazes and measured to center of trees at lower blaze:

- White Oak, 15 ins. diam., brs. N11½°E, 46.7 feet. Record; 45.6 feet.
- White Oak, 6 ins. diam., brs. S9½°W, 114.2 feet. Record; S9°40'W, 114.5 feet.
- White Oak, 9 ins. diam., brs. N18½°W, 40.7 feet. Record; 39.9 feet.

July 11, 1985
R. Frost
S. Nelson
T. Newcomb

Edward McGinty
County Surveyor

P. -218