

## FIRST RE-ESTABLISHMENT

GCDB 700600

Corner common to Sections 1 and 12, Township 36 South, Range 1 East, W.M. and Sections 6 and 7, Township 36 South, Range 2 East, W.M.

Set a 1"x36" galvanized iron pipe 28" in the ground with a 2½" bronze cap stamped:

T.36 S, R1 - 2E.  
1 | 6  
Sec. ——— Cor.  
12 | 7  
C.S.  
1971

For corner, from which:

- The original bearing tree (now a 14" Hollow Black Oak) bears N43°W, 33.4 feet to the center;
- The original bearing tree (now a 14" Black Oak with scribe visible) bears S20¼°E, 120.1 feet to the face of the lower blaze. (Record: 10" Black Oak, S18°E, 120.1 feet)
- The original bearing tree (now a Pine stump hole) bears S65°W, 110.5 feet to the center;
- Scattered Pine remains checks the position for the original Northeast bearing tree.

Mark new trees as follows:

- A 9" White Oak, scribed "CS-BT" bears N 32¾° E, 23.3 feet to the face of the lower blaze;
- A 7" White Oak, scribed "CS-BT" bears S 64¾° W, 86.5 feet to the face of the lower blaze.

January 28, 1971  
Gary Kaiser, Deputy County Surveyor  
Lloyd Shreeve