

**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 1 AND 6 ONLY
GCDB 700700**

Township corner common to Sections 1 and 6, Township 36 South, Range 1 and 2 East, WM
V = 21°

From the following evidence and at the location described below, I set a 1x36 ins. G.I. pipe 28 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County
T36S
R1E R2E
S1 | S6
1974

Original BTs marked by Ives and Hyde in 1854 found as follows:

- A Black Oak, 19 ins. diam., with healed blaze, bears record, N46½°E, 62.7 feet to estimated face.
- A Yellow Pine, 37 ins. diam., containing scribe marks in exposed face, including "R", "36", and "S6", bears S8½°E, 114.7 feet to scribed face. Record, S9°E, 114.18 feet (**Note:** This is also the original S.W. BT for the standard corner to Sections 31 and 36.)
- A Black Oak, 21 ins. diam., with healed blaze (located on the east- west fence line), bears record, N76°W, 19.14 feet to estimated face of blaze.

I mound stones around corner, marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- A Black Oak, 5 ins. diam., bears S16°W, 43.5 feet.
- A Ponderosa Pine, 5 ins. diam., bears N63°W, 30.3 feet.
- The standard corner of Sections 36 and 31, bears East 66.0 feet.

February 18, 1974
B. Malotte
R. Frost
V. Gardener: Witness

Approved by: Edward McGinty
County Surveyor