

**FIRST RE-ESTABLISHMENT**

**DLC40NNE**

**GCDB 806200**

Most Northerly NE corner D.L.C. #40, Township 36 South, Range 1 East.

Found original BT to NW with scribe visible,

From which set 1½" x 36" galvanized pipe 35" in the ground for corner,

From which:

- A 12" white oak scribed C.S.-BT bears N.89°15'E., 86.5 feet.
- A 24" black oak scribed C.S.-BT bears S.30°30'W., 129.9 feet.
- A 36" black oak scribed C.S.-BT bears N.61°30'W., 138.6 feet.

February 18, 1931  
Boyden, Deputy County Surveyor  
Tice & Pettegrew, Chainmen

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

DLC40NNE

GCDB 806200

North-northeast corner of Donation Land Claim No. 40, Township 36 South, Range 1 East, W.M.

Found no evidence of the 1½" iron pipe corner monument set for corner by Deputy County Surveyor, C. Z. Boyden on the first re-establishment on February 18, 1931.

Found stumps for the Northwest and Southeast bearing trees, and a stump hole for the Southwest bearing tree as established on the first re-establishment, which locations agree favorably with the record.

Found the original bearing tree (now a 19" White Oak) with old faces deteriorated with no remaining scribe marks

From which set a 1"x36" galvanized iron pipe with bronze cap stamped:

T. 36 S. R.1 E.  
N.N.E. Cor.  
40 | D.L.C.  
C.S.  
1970

36" in the ground for corner, from which:

- Said original bearing tree bears N 24° W, 66.7 feet to the face;
- Scribed an 18" White Oak, "CS-BT" which bears N44°03' W, 139.6 feet to the face of the lower blaze;
- Scribed a 10" White Oak, "CS-BT" which bears N45°46' E, 82.8 feet to the face of the lower blaze;
- Scribed a 10" Yellow Pine, "CS-BT" which bears S29°54' W, 116.4 feet to the face of the lower blaze.

December 28, 1970  
G. D. Kaiser, Deputy County Surveyor  
Dan Phillips