

FIRST RE-ESTABLISHMENT

GCDB 100100

Corner common to Sections 36, Township 36 South, Range 2 East, and Sections 31, Township 36 South, Range 3 East, W.M. $V = 19\frac{1}{2}^\circ$

Found, firmly set, in a ring of stone, the 21 x 16 x 8 ins. stone (record, 18 x 12 x 8 ins.) placed by M.L. McCall in 1880, perpetuating the corner set by Ives and Hyde in 1854. Said stone is marked with 3 notches on the South and 5 on the East sides.

I replace the above with a 1 x 36 ins. G.I. pipe set 29 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1975
T36S R2-3E
36 | 31
—
6
T37S

BTs recorded by McCall, found as follows:

- A White Oak stump shell about 12 ins. diam., containing scribed "6" and "31" bears N56½°E, 97.2 feet to exposed lower face.
- White Oak, 17 ins. diam., with healed blazes, bears S40½°E, 177.2 feet to estimated lower face.
- Stump holes found at record location of N.W. and S.W. BTs.

I deposit found stones alongside corner as a memorial, marked new tree C.S. BT and take measurements to center of tree at lower blaze:

- Douglas Fir, 10 ins. diam., bears N45¾°E, 26.1 feet.
- White Oak, 6 ins. diam., bears S37°W, 28.4 feet.
- Ponderosa Pine, 20 ins. diam., bears N21¼°W, 35.8 feet.
- The closing corner (Section 1 and 6) bears Westerly 143.5 feet.
- A 24 ins. diam., Douglas Fir, with attached location marker, bears S23½°W, 13.2 feet.

September 12, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor