

FIRST RE-ESTABLISHMENT

GCDB 100240

Quarter corner common to Sections 25 and 30, Township 36 South, Range 2 and 3 East, W.M.
 $V = 16^\circ$

Found original S.W. BT, marked by Ives and Hyde in 1854, now a Fir snag, 48 ins. diam., and approximately 15 feet high, containing scribe marks in partially opened upper face.

At record bearing and distance, $S40^\circ W$, 26.4 feet I set a 1 in. x 36 ins. G.I. pipe, 29 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

T36S
 $\frac{1}{4}S$
R2E R3E
25 | 30
C.S.
1973

From which:

- The rotted stump of the original N.E. BT with section of Fir alongside containing scribed "BT" bears record, $N57^\circ E$, 13.86 feet.

I marked new trees C.S. BT, and take measurements to center of trees at lower blaze:

- A Douglas Fir 24 ins. diam., bears $S3^\circ E$, 20.7 feet.
- A Douglas Fir 21 ins. diam., bears $S86\frac{1}{2}^\circ W$, 22.5 feet.

September 13, 1973
E. Graham
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100240

Quarter corner common to Section 25, Township 36 South, Range 2 East and Section 30, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 4 ins., the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1973, marked:

T36S
¼S
R2E | R3E
25 | 30
C.S.
1973

Original bearing trees recorded by Ives and Hyde of the GLO in 1854, found and re-measured:

- Fir snag 48 ins. diam. with opened rotted face brs. record; S40°W, 26.4 ft. to face.
- Fir debris with faint "BT" on detached weathered face brs. record; N57°E, 13.9 ft. to center of remains.

Bearing trees recorded on said 1st Re-establishment found with healed double blazes and measured to center at lower blaze:

- D. fir, now 36 ins. diam. brs. record; S3°E, 20.7 ft.
- D. fir, now 33 ins. diam. brs. record; S86½°W, 22.5 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- D. fir 17 ins. diam. brs. N89°E, 8.0 ft.
- No trees within limits in northwest quadrant.

Corner lies approx. 650 ft. south along blazed line from 4-wheel drive spur road.

August 31, 2009

H. Durkee

Kerry K. Bradshaw
Jackson County Surveyor

P. – 199

V. – 12°20'