

**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 1 AND 6 ONLY
GCDB 100700**

Standard corner for Section 1, Township 36 South, Range 2 East and Section 6, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 6 ins. and in a mound of stones, the 2½ ins. diam. galvanized iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1963, marked:

S1	S6
R2E	R3E
T36S	
S.C.	
1963	

Bearing trees recorded by the BLM in 1963, found and measured to center of trees at base:

- Sawed w. fir stump with partially healed single blaze revealing scribe marks "T36S R3E SC BT" bears Record: S42°W, 25.7 feet.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Cedar 9 ins. diam. bears S3½°E, 58.8 feet.
- White Fir 6 ins. diam. bears S64°W, 22.0 feet.

Corner lies approximately 200 feet easterly of gravel road at bend northerly and westerly,

May 16, 2006
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 79
V. - 15°50'

**SECOND RE-ESTABLISHMENT
GCDB 100700**

Standard corner common to Section 1, Township 36 South, Range 2 East and Section 6, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 6 ins. in a mound of stones, the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1963, marked:

S1 | S6
R2E R3E
T36S
S.C.
1963

Bearing tree recorded by the BLM in 1963,

- A down rotted fir stump with scribe marks "T36SR3E SC BT" on partially healed face brs. record; S 42° W, 25.7 ft. to center of stump hole.

Bearing trees recorded on 1st Re-establishment in 2006, found with partially healed double blazes revealing scribe marks "CS" "BT" and measured to center at lower blaze:

- Cedar, now 10 ins. diam. brs. record; S 3½° E, 58.8 ft.
- W. fir now 6 ins. diam. and broken off approx. 10 ft. high by logging brs. record; S 64° W, 22.0 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- W. fir 8 ins. diam. brs. S 88¼° W, 37.8 ft.

Corner lies approx. 200 ft. easterly of bend in gravel road. C. – northerly and westerly.

October 16, 2008

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. – 202
V. – 14°20'