

FIRST RE-ESTABLISHMENT

GCDB 140200

Quarter corner common to Sections 30 and 31, Township 36 South, Range 3 East, W.M. $V = 20^\circ$

Found original S.W. BT, a Black Oak, now 18 ins. diam., containing scribed "BT" in lower face. From which evidence and at record bearing and distance, $S31^\circ W$, 104.94 feet.

I drove a $2\frac{1}{2}$ ins. bronze disc in a drilled hole, flush with bedrock, marked:

T36S R3E
30
 $\frac{1}{4}S$ —
31
C.S.
1973

At record location of original N.W. BT, Black Oak remains were in evidence.

- A granite stone, with probable chisel marks and comparable in size with that of corner.

I deposit said stone alongside corner and marked a new tree C.S. BT

- A Black Oak, 14 ins. diam., bears $S5^\circ W$, 84.9 feet to center of tree at lower blaze.

September 13, 1973
E. Graham
B. Malotte

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 140200

Quarter corner common to Sections 30 and 31, Township 36 South, Range 3 East, W.M.

Found at the corner, set in a crack of a rock, in the dirt, at the base and on the East side of a rock outcropping, the 2½ ins. diam. brass cap, recorded as set on First Re-establishment in 1973 and marked:

T36S R3E
30
¼S —
31
CS
1973

Remove said brass cap and reset, at the same position, in a drill hole, a 5/8 x 6 ins. rebar, projecting 1 in., drove over top of said rebar, a 1 x 6 ins. galvanized iron pipe, projecting 5 ins.

Set in rock-tite, in top of said 1 x 6 ins. galvanized iron pipe, the said brass cap, re-marked:

T36S R3E
30
¼S —
31
1991
1973

Single remaining original bearing tree, recorded as marked by Rufus Moore in 1883, found:

- Black Oak, now 18 ins. diam., with previously opened lower blaze, containing rotted and faint scribe marks, "BT", bears S31°W, 105.7 feet to center of tree at lower blaze. Record: S31°W, 104.94 feet.

Bearing tree recorded as marked on said First Re-establishment found:

- Black Oak, now 16 ins. diam., with double healed blazes, bears S3°E, 80.45 feet to center of tree at lower blaze. Record: S5°W, 84.9 feet. (**Note:** Found, in field notes, an error in slope reduction. Level distance should be 80.23 feet, not 84.9 feet.).

Mark new tree "CS" "BT":

- Ponderosa Pine 23 ins. diam., which bears S60½°E, 111.65 feet to center of tree at lower blaze.

Mark additional new tree "CS" only:

- Black Oak, 8 ins. diam., which bears N74¼°W, 15.6 feet to center of tree at lower blaze.

Corner lies on 53% Southerly slope, on Easterly edge and at the base of rock out-cropping.

July 18, 1991
H. Durkee, Tech.
T. Newcomb, Tech.

Verlyn Thomas
County Surveyor

V = 17°
P.-52