

FIRST RE-ESTABLISHMENT
GCDB 140600

SPECIAL CORNER

Quarter corner common to Sections 6 and 7, Township 36 South, Range 3 East, W.M.

Found at the proportioned position, exposed 6 ins. in a mound of stones, the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1982, marked:

T36S R3E
S6
¼ —
S7
1962
1982

Bearing trees recorded by the BLM in 1992, found dead, down and rotted and measured to center of stump holes:

- Fir approx. 20 ins. diam. brs. record; N36¾°E, 19.1 ft.
- Fir approx. 14 ins. diam. brs. record; S55¼°W, 11.2 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- P. Pine 9 ins. diam. brs. N60°E, 15.0 ft.
- P. Pine 8 ins. diam. brs. S74½°E, 19.9 ft.
- P. Pine 7 ins. diam. brs. S21¼°W, 21.5 ft.
- No trees practical in northwest quadrant.

Corner lies approx. 600 ft. north of gravel logging road.

October 29, 2012
H. Durkee

Scott Fein
Deputy Jackson County Surveyor

P. – 68
V. – 15°25'