


## FIRST RE-ESTABLISHMENT

GCDB 200240

Quarter corner common to Sections 29 and 30, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 4 ins. and in a mound of stones, the 2½ ins. diam. galvanized iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1963, marked:



Original bearing trees recorded by Rufus Moore in 1883, found and measured to center of trees at base:

- Fir snag, 36 ins. diam. with double healed blazes, bears S85°E, 30.9 feet. Record: 29.7 feet to face.
- Fir snag, 30 ins. diam. with partially healed upper blaze revealing scribe marks "4S" bears S39°W, 6.5 feet. Record: S41°W, 5.94 feet to face.

Bearing trees recorded by the BLM in 1963, found with healed single blazes and measured to center of trees at base;

- Fir, now 21 ins. diam. bears Record: N60°E, 11.88 feet.
- Fir, now 32 ins. diam. bears Record: N65°W, 71.9 feet.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Douglas Fir, 12 ins. diam. bears N35½°W, 10.9 feet.

Corner lies westerly and downhill approximately 500 feet from graveled spur road.

August 16, 2005

H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 118  
V. - 17°30'