

FIRST RE-ESTABLISHMENT

GCDB 200340

Quarter corner common to Sections 19 and 20, Township 36 South, Range 3 East, W.M. $V=21^\circ$

From the following evidence at the location described below, I set a $\frac{5}{8}$ x 12 ins. re-steel rod, 7 ins. deep with a $2\frac{1}{2}$ ins. bronze disc marked:

Jackson County 1975
T36S R3E
 $\frac{1}{4}$ S
19 | 20

- A BT marked by BLM in 1956, a Douglas Fir, now 42 ins. diam., with healed blazes, bears Record: $S84\frac{1}{2}^\circ W$, 58.74 feet to center.
- The N.E. BLM tree along with both original BTs, now lost in road construction activities.
- A witness tree recorded on Survey No. 1364, on file, a Yew, now 13 ins. diam., scribed "301" and "BT" in exposed faces bears $N26\frac{3}{4}^\circ E$, 54.8 feet to scribed upper face. Record, $N23\frac{1}{2}^\circ E$, 54.8 feet.
- I set a $\frac{7}{8}$ x 19 ins. re-steel rod, 3 ins. deep, which bears $N59^\circ 05'E$, 16.33 feet.
- A $\frac{7}{8}$ x 22 ins. re-bar set 3 ins. deep bears $S59^\circ 05'W$, 14.85 feet.

Corner lies in center of Wasson Canyon Road, about 175 feet Westerly of center of road at switchback.

April 29, 1975
R. Frost
G. Cunningham

Approved by: Edward McGinty
County Surveyor