

FIRST RE-ESTABLISHMENT

GCDB 300140

Quarter corner common to Sections 32 and 33, Township 36 South, Range 3 East, W.M. $V = 20\frac{3}{4}^\circ$

Found Basalt stone (16x14x8 ins.) firmly set in the ground and marked as recorded by R. Moore in 1883, with "¼" on West face.

I replaced said stone with a 1 in. x 36 ins. G.I. pipe set flush in the ground with a 2½ ins. bronze disc marked:

T36S R3E
S¼
32 | 33
C.S.
1973

Original BTs were found as follows:

- A Maple containing scribe marks, 18 ins. diam., bears S72°E, 51.3 feet. Record: S73°E, 51.6 feet.
- A Pine, 43 ins. diam., containing scribe marks in upper blaze, bears S61°W, 42.7 feet. Record: S60°W, 42.9 feet.

I mound stones around corner, deposit original stone alongside as memorial, mark the following trees C.S. BT, and take measurements to center of trees at lower blaze:

- A Black Oak, 7 ins. diam., bears N6½°E, 19.0 feet.
- A Douglas Fir, 12 ins diam., bears S56°W, 10.2 feet.

September 12, 1973
E. Graham
B. Malotte

Approved by: Edward McGinty
County Surveyor