

FIRST RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 36 South, Range 3 East, W.M.
 $V = 20\frac{3}{4}^\circ$

Found the stone (18 x 10 x 6 ins.) marked by R. Moore in 1883, apparently having been dislodged from its recorded position.

From the following original evidence and at a location as noted below, I set a 1 x 36 ins. G.I. pipe, 30 ins. in the ground with a 2½ ins. bronze disc marked:

T36S	R3E
S29	S28
S32	S33
C.S.	
1973	

From which:

- An original BT, a Pine, now 50 ins. diam., containing scribed "3E S33" in partially open face, bears record, S38°E, 62.7 feet.
- An original BT, a Fir, now 36 ins. diam., with healed blaze, bears record N55°W, 8.58 feet.
- At record location of NE and SW BTs, stump depressions containing Fir fragments were found

I deposit original stone alongside for a memorial, marked the following trees C.S. BT, and take measurements to center of trees at lower blaze:

- A Douglas Fir, 12 ins. diam., bears N33°E, 21.7 feet.
- A W. Fir, 8 ins. diam., bears S38°E, 8.1 feet.
- A Douglas Fir, 18 ins. diam., bears S71½°W, 21.1 feet.

Corner is located approximately 100 feet West of N-S fence line.

September 12, 1973
E. Graham
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 36 South, Range 3 East, W.M.

Corner monument destroyed by fire trail construction.

From the following evidence, set at the corner position, a 2 x 30 ins. galvanized iron pipe with a 3½ ins. diam. brass cap protruding 8 ins. and marked:

JACKSON COUNTY SURVEYOR
T36S R3E
S29 | S28
—•—
S32 | S33
2005

And raised a mound of stones.

Single remaining original bearing tree recorded by R. Moore in 1883, a large, burnt pine stump, bears Record: S38°E, 62.7 feet to estimated face.

Bearing trees recorded on First Re-establishment in 1973, found with double healed blazes and measured to center of trees at lower blaze:

- Douglas Fir snag bears N32°E, 21.7 feet. Record: N33°E.
- Douglas Fir, now 25 ins. diam. bears S71°W, 21.1 feet. Record: S71½°W.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Douglas Fir 6 ins. diam. bears S78°E, 26.8 feet.
- White Fir 10 ins. diam. bears N13°E, 51.9 feet.
- 4 feet high steel fence post with "LAND SURVEY MONUMENT" sign bears north, approximately 2 feet.

Corner lies east approximately 50 feet from end of spur road.

August 10, 2005

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 116
V. - 15°30'