

FIRST RE-ESTABLISHMENT

GCDB 300240

Quarter corner common to Sections 28 and 29, Township 36 South, Range 3 East, W.M. $V = 19\frac{1}{2}^\circ$

Found basalt stone (18x12x6ins.) firmly set and marked as described by R. Moore in 1883, with "¼" on the West face.

In the absence of suitable trees to mark, Moore "raised" a pile of stones, which are in evidence 5 feet West of the corner.

I replaced said stone with a 1 x 36 ins. G.I. pipe set 27 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R3E
¼
29 | 28
C.S.
1973

I marked the following trees C.S. BT, and take measurements to center of trees at lower blaze:

- A White Fir, 13 ins. diam., bears N39°W, 22.5 feet.
- A White Fir, 21 ins. diam., bears N69°E, 15.1 feet.

Original stone deposited alongside as memorial to corner, which lies 75 feet West of N-S fence line.

September 12, 1973
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300240

Quarter corner common to Sections 28 and 29, Township 36 South, Range 3 East, W.M.

Found at the corner position, protruding 8 ins. and in a mound of stones, the 1 in. diam. galvanized iron pipe with a 2½ ins. brass cap set on First Re-establishment in 1973 and marked:

T36S R3E
¼
29 | 28
C.S.
1973

Single remaining bearing tree marked on said First re-establishment,

- A fir snag, now 22 ins. diam. with a partially healed lower blaze revealing scribe marks "BT" bears Record: N 69° E, 15.1 feet to center of tree at lower blaze.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- A White Fir 18 ins. diam. bears N57°W, 2.9 feet.

Set references, 5/8 x 24 ins. rebar with 1½ ins. diam. bronze caps, protruding 2 ins. and marked:

JACKSON COUNTY

SURVEYOR

Bears:

- N69°E, 13.5 feet (at base of old bearing tree)
- N4°W, 20.2 feet (in north-south fence line)

Corner lies approximately 3 feet east of north-south fence line and approximately 200 feet west of logging Road

April 20, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 42
V. - 16°