

FIRST RE-ESTABLISHMENT

GCDB 300400

Section corner common to Sections 16, 17, 20 and 21, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 16 ins. and in a mound of stones, the 2 ins. diam. galvanized iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1956, marked:

T36S R3E	
S17	S16

S20	S21
1956	

Single remaining original bearing tree recorded by Rufus Moore in 1883, a fir snag with healed blazes bears Record: N29°E, 17.8 feet.

Bearing trees recorded by BLM in 1956, found with healed single blazes and measured to center of trees at base:

- Fir snag, dead and down bears Record: S48°E, 17.8 feet to center of stump hole.
- Fir snag bears S51½°W, 14.5 feet. Record: S50½°W.
- Fir snag bears Record: N33°W, 35.6 feet.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Fir 13 ins. diam. bears S21°W, 57.2 feet.
- White Fir 6 ins. diam. bears N56¼°W, 37.0 feet.
- White Fir 16 ins. diam. bears S60°E, 12.1 feet.
- No trees of size in northeast quadrant within limits.

Corner lies in seasonal creek bed, approximately 3 feet west of barbed wire fence line and 20 feet south of old 4-wheel drive road.

February 21, 2006

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 24

V. - 15°05'