

## FIRST RE-ESTABLISHMENT

GCDB 300640

Quarter corner common to Sections 4 and 5 of Township 36 South, Range 3 East, W.M.

Found at corner position , exposed 8 ins., in a mound of stones, the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1962 and marked:

T36S R3E  
S5 | S4  
1962

Single remaining original bearing tree recorded by Rufus Moore of the GLO in 1883 found with a healed blaze and measured to center at base;

- Madrone now 24 ins. diam. brs. N22°W, 19.0 ft. record; 17.2 ft.

Bearing trees recorded by the BLM in 1962 found with healed blazes and measures to center at base;

- W. fir now 18 ins. diam. brs. N45°E, 38.7 ft. record; 38.3 ft.
- D. fir now 20 ins. diam. brs. N38°W, 17.8 ft. ; record; N40°W

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

- Cedar 9 ins. diam. brs. S61°E, 47.8 ft.
- Cedar 11 ins. diam. brs. S78½°W, 24.9 ft.

Corner lies atop cut bank on north side of gravel road.

October 28, 2009

B. Beeman  
H. Durkee

Kerry K. Bradshaw  
Jackson County Surveyor

P. – 2246  
V. – 16°45'