

FIRST RE-ESTABLISHMENT

CLOSING CORNER TO SECTIONS 4 AND 5 ONLY

GCDB 300700

Closing corner common to Sections 4 and 5, Township 36 South, Range 3 East, W.M. $V = 20\frac{1}{2}^\circ$

Found S.W. BT, recorded on 1883 resurvey by R. Moore, now a Fir snag, 21½ ins. diam., approximately 15 feet high, containing scribed "CC T36S R3E S5" in upper face and scribe marks visible in partially opened lower face.

From which evidence and at record bearing and distance, $S19^\circ W$, 42.24 feet, I set a 1 in x 36 ins. G.I. pipe, 10 ins. below the road surface, with a 2½ ins. bronze disc marked:

T35S
Clos. Cor.
S5 | S4
T36S R3E
C.S.
1973

I marked the following trees C.S. BT, and take measurements to center of trees at lower blaze:

- A Douglas Fir, 12 ins. diam., bears $S4\frac{1}{2}^\circ E$, 75.2 feet.
- A Douglas Fir, 10 ins. diam., bears $S36\frac{1}{2}^\circ W$, 38.5 feet.

August 15, 1973
E. Graham
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
CLOSING CORNER TO SECTIONS 4 AND 5 ONLY
GCDB 300700**

Closing corner common to Sections 4 and 5, Township 36 South, Range 3 East, W.M.

Fd. the 2½ ins. bronze disc set on first Re-Establishment dated 1973, 8 ins. below ground surface, mkd:

T35S
Clos. Cor.
S5 | S4
T36S R3E
C.S.
1973

Found bearing trees made on First Re-Establishment with healed blazes and measured to center of trees at lower blaze:

Douglas Fir, 12 ins. diameter, brs. S06°05'40"E, 75.2 ft. Record S4½°E.

Douglas Fir, recorded as bearing S36½°W, 38.5 ft. found dead and down.

New references taken:

Cedar, 22 ins. diam. brs. N03°38'26"W, 17.42 ft. to center of tree at base. BT has healed blaze, marked for Angle Point on 1975 Re-establishment.

Fd. 3½ ins. diam. BLM Brass Cap mkd.

T35S R3E
S32 | S33
S5
T36S
1977 brs. S 88°30'06" W, 198.80 ft.; Record, S89°11'W, 198.66 ft.

Fd. 3½ ins. diam. BLM Brass Cap, found in mound of stone, mkd:

AP
T35S R3E
S33
S4
T36S
1977 brs. S 88°17'43" E, 28.07 ft.; Record, East 27.72 ft.

Basis of Bearing is measured from found AP common to T35S R3E S33 and T36S R3E S4 W.M. and found Cedar BT as referenced in 1975 re-establishment.

Corner lies at northeasterly edge of southerly most road; approximately 80 ft. east of fork.

July 27, 2017
B. Paull
J. Hall

Scott Fein
County Surveyor

P-