

## FIRST RE-ESTABLISHMENT

GCDB 340300

Quarter corner common to Sections 21 and 28, Township 36 South, Range 3 East, W.M.  $V = 19\frac{1}{2}^\circ$

Found original N.W. BT, now a Fir snag, 18 ins. diam., approximately 6 feet high, containing scribed " $\frac{1}{4}$ S"

From which evidence and at record bearing and distance,  $N67^\circ W$ , 14.52 feet, I set a 1 in x 36 ins. G.I. pipe, 30 ins. in the ground, with a  $2\frac{1}{2}$  ins. bronze disc marked:

T36S R3E  
21  
 $\frac{1}{4}$ S —  
28  
C.S.  
1973

The basalt stone (22 x 12 x 10 ins.) marked " $\frac{1}{4}$ " by R. Moore in 1883, was found nearby, having obviously been removed from its original position. Said stone deposited alongside corner as memorial.

I place a mound of stone around corner and marked the following trees, C.S. BT:

- A W. Fir, 12 ins. diam., bears  $N75^\circ E$ , 29.5 feet to center of tree at lower blaze.
- A W. Fir, 19 ins. diam., bears  $S4^\circ E$ , 34.0 feet, to center of tree at lower blaze.

Location marker placed on road, approximately 250 feet N. of corner.

August 7, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT**  
**GCDB 340300**

Quarter corner common to Sections 21 and 28, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 6 ins. in a mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1<sup>st</sup> Re-establishment in 1973, marked:

T36S R3E  
21  
¼S—  
28  
C.S.  
1973

Bearing trees recorded on said 1<sup>st</sup> Re-establishment found with healed double blazes and measured to center at lower blaze:

- W. Fir, now 16 ins. diam. brs. record; N 75° E, 29.5 ft.
- Fir high-stump brs. record; S 4° E, 34.0 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- W. Fir 11 ins. diam. brs. S 76¼° E, 23.8 ft.
- W. Fir 6 ins. diam. brs. N 62¼° W, 13.7 ft.
- D. Fir 11 ins. diam. brs. S 49½° W, 8.7 ft.

Corner lies approx. 200 ft. south of logging spur road.

October 28, 2010  
H. Durkee

Kerry Bradshaw  
Jackson County Surveyor

P. – 214  
V. – 16°10'