

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 36 South, Range 3 East, W.M.
 $V = 21\frac{3}{4}^\circ$

A basalt stone (14 x 14x 5 ins.) marked as noted by R. Moore in 1883, with 1 notch on the S face and 3 notches on the E, was found in a pile of stones alongside a $\frac{5}{8}$ in. I-pin, with an aluminum cap marked:

MEDCO	
28	27
<hr/>	
33	34

I replaced said pin with a 1 in. x 36 ins. G.I. pipe, set 20 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

T36S R3E	
S28	S27
<hr/>	
S33	S34
C.S.	
1973	

From which evidence of original BTs was found as follows:

- A Pine, 26 ins. diam., containing scribe marks in opened lower face, bears $N26^\circ E$, 59.4 feet on slope to scribed face. Horizontal distance, 59.05 feet. Record: $N26^\circ E$, 59.4 feet.
- Oak sprouts at record location of N.W. BT, $N24^\circ W$, 46.86 feet.
- The rotted Pine stump of original S.E. BT bears record, $S28^\circ E$, 35.64 feet.

I marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- A W. Fir, 20 ins. diam., bears $N35^\circ E$, 19.8 feet.
- A Douglas Fir, 13 ins. diam., bears $S20^\circ E$, 29.7 feet.
- A Douglas Fir, 15 ins. diam., bears $S29^\circ W$, 21.8 feet.
- A W. Fir, 9 ins. diam., bears $N55^\circ W$, 24.6 feet.

September 10, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor