

FIRST RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 36 South, Range 3 East, W.M. $V = 19\frac{1}{2}^\circ$

Found the basalt stone (8 x 12 x 18 ins.) firmly set in the ground and marked "¼" on the West face, as described by R. Moore in 1883.

Evidence of recorded trees was found as follows:

- The stump depression and Chinquapin fragments of the original N.E. BT bears record, N82°E, 9.24 feet.
- The decomposed stump of the original S.W. BT bears Record: S85°W, 3.96 feet.
- A Fir, located as Moore described, 1½ chains North of the corner was found A Section of this tree now down, contains 2 axed notches, along with old blaze marks

I replaced the original stone with a 1 in. x 36 ins. G.I. pipe set 32 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R3E
¼S
21 | 22
C.S.
1973

A Chinquapin, 10 ins. diam., with attached USFS location marker dated "5-17-51" bears S24°W, 19.8 feet.

I place stones around corner, deposit original stone alongside as a memorial and marked new trees C.S. BT:

- A W. Fir, 9 ins. diam., bears N3½°E, 27.3 feet to center of tree at lower blaze.
- A Yew, 7 ins. diam., bears N78°W, 20.6 feet to center of tree at lower blaze.

Corner lies at intersections of N-S and W Blaze line.

September 6, 1973
E. Graham
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT
GCDB 400340

Quarter corner common to Sections 21 and 22, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 4 ins. in a mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1973, marked:

T36S R3E
¼S
21 | 22
C.S.
1973

Bearing trees recorded on said 1st Re-establishment, found and measured to center at lower blaze:

- W. Fir, now 24 ins. diam. with healed double blazes, brs. N3°E, 27.3 ft. Record; N3½°E.
- Yew, now 10 ins. diam. with scribe marks "CS" "BT" in partially healed double blazes brs. record; N78°W, 20.6 ft.
- A Yew snag (reported as a Chinquapin) with a USFS "K" tag dated 1951 brs. record; S24°W, 19.8 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Yew 7 ins. diam. brs. S24°E, 14.7 ft.
- W. Fir 7 ins. diam. brs. S76½°W, 20.3 ft.

Corner lies approx. 200 ft. west of end of spur road.

November 1, 2010

H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 215
V. – 15°30'