

FIRST RE-ESTABLISHMENT

GCDB 440300

Quarter corner common to Sections 22 and 27, Township 36 South, Range 3 East, W.M. V = $19\frac{1}{2}^\circ$

Found original stone (20 x 12 x 4 ins.) with " $\frac{1}{4}$ " marked on N. Face as set by R. Moore in 1883.

I replaced said stone with a 1 in. x 36 ins. G.I. pipe, set 28 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

T36S R3E
22
 $\frac{1}{4}$ S —
27
C.S.
1973

From which:

- An original BT, a White Fir, now 27 ins. diam., with scribe marks visible in partially opened face, bears record, N 54° W, 17.82 feet.
- An original BT, a Yew, now 14 ins. diam., containing scribed " $\frac{1}{4}$ S", alive but tipped over, the base of which bears Record: S 50° E, 11.22 feet.
- A $\frac{5}{8}$ in. diam., re-steel rod with aluminum cap marked:

MEDCO
22
 $\frac{1}{4}$ S —
27

Bears S 33° W, 4.13 feet.

I mound stones around corner, deposit original stone alongside as memorial and marked the following trees C.S. BT:

- A Chinquapin, 18 ins. diam., bears N $41\frac{1}{2}^\circ$ E, 27.8 feet to center of tree at lower blaze.
- A Yew, 16 ins. diam., bears S 67° W, 16.0 feet, to center of tree at lower blaze.

August 8, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 440300

Quarter corner common to Sections 22 and 27, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 6 ins. in a mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1973, marked:

T36S R3E
22
¼S ———
27
C.S.
1973

Original bearing trees recorded by Rufus Moore of the GLO in 1883, found and measured to center at base:

- Sawed, rotted Fir stump brs. record; N 54° W, 17.8 ft.
- Rotted yew remains brs. record; S 50° E, 11.2 ft.

Bearing trees recorded on said 1st Re-establishment, found and measured to center at lower blaze:

- Chinquapin, now 24 ins. diam. with a scribed "S" in a partially healed upper blaze brs. record; N41½°E, 27.8 ft.
- A Yew, now 21 ins. diam. with a scribed "S" in a partially healed upper blaze brs. record; S67°W, 16.0 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Yew 8 ins. diam. brs. N 64° W, 7.1 ft.
- Thick brush in southeast quadrant. No new trees taken.

Corner lies approx. 75 ft. northeasterly of landing at end of spur road.

November 1, 2010

H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 216

V. – 15°45'