

FIRST RE-ESTABLISHMENT

GCDB 500300

Section corner common to Sections 22, 23, 26 and 27, Township 36 South, Range 3 East, W.M.
 $V = 20^\circ$

From the following evidence of trees recorded as marked by R. Moore in 1883, I set a 1 in. x 36 ins. G.I. pipe, 16 ins. in the ground with a 2½ ins. bronze disc marked:

T36S R3E	
S22	S23
— —	
S27	S26
C.S.	
1973	

From which:

- The stump hole of a down and rotted Fir, containing illegible scribe marks, bears $N32^\circ E$, 13.2 feet. Record: $N22^\circ E$, 13.2 feet.
- The stump hole of a dead and down Pine, 8 ins. diam., containing scribed "T36S R3E S26", bears $S51^\circ E$, 14.2 feet. Record: $S51^\circ E$, 13.2 feet. The 1883 record notes this tree to be a 9 ins. diam. Fir at time of marking.
- A Fir snag, 48 ins. diam., approximately 20 feet high, with healed blazes, bears record, $S41^\circ W$, 35.64 feet.
- The stump hole of a down and dead Cedar, 8 ins. diam., containing scribed "T36S R3E S22", bears record, $N17^\circ W$, 15.84 feet.

I marked new trees, C.S. BT, and take measurements to center of trees at lower blaze:

- A Cedar, 18 ins. diam., bears $N24^\circ E$, 37.2 feet.
- A Cedar, 20 ins. diam., bears $S30^\circ E$, 98.8 feet.
- A Cedar, 24 ins. diam., bears $S19^\circ W$, 83.7 feet.
- A S. Pine, 25 ins. diam., bears $N16^\circ W$, 79.5 feet.

I mound stones around corner and place the original stone, found nearby, broken and displaced, alongside corner for a memorial.

A 5/8 in. diam. re-steel rod projecting 10 ins., with an aluminum cap marked:

MEDCO	
22	23
— —	
27	26

Bears $S68^\circ E$, 1.36 ft.

August 13, 1973
B. Malotte
T. Newcomb (USFS)

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500300

Section corner common to Sections 22, 23, 26 and 27, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 10 ins. and in a mound of stones, the 1 in. diam. galvanized iron pipe with a 2½ ins. diam. brass cap, set on First Re-establishment in 1973, marked:

T36S R3E
S22 | S23
—•—
S27 | S26
C.S.
1973

Bearing trees recorded on First Re-establishment, found and measured to center of tree at lower blaze:

- Sawed cedar stump, now 20 ins. diam. with partially healed lower blaze containing scribe marks "BT" bears Record: N 24° E, 37.2 feet.
- Sawed cedar stump, now 27 ins. diam. with partially healed blazes containing scribe marks "CS" "BT" bears Record: S 19° W, 83.7 feet.
- Sawed S. pine buckskin stump, now 24 ins. diam. with healed blazes, not measured due to new growth of brush and tree. Record: N 16° W, 79.5 feet.

Mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Fir 13" diam. bears N 88¼° W, 19.9 feet.
- White Fir 7" diam. bears N 6° W, 35.0 feet.
- Cedar 5" diam. bears S 1½° W, 18.9 feet.
- Cedar 8" diam. bears N 77½° E, 47.3 feet.
- 1½ ins. diam. Medco aluminum cap, exp. 6 ins. bears S 68° E, 1.36 feet near base of mound of stones.

Corner lies approximately 40 feet westerly of graveled spur road.

May 11, 2005

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 52
V. - 16°50'