

**FIRST RE-ESTABLISHMENT**

**GCDB 540500**

Quarter corner common to Sections 11 and 14, Township 36 South, Range 3 East, W.M.

Found projecting 2 ins., in a mound of stones, the standard 3 ins. diam. BLM brass cap marked:

T36S R3E  
S11  
¼S —  
S14  
1962

On a 2 ins. diam. iron pipe.

Bearing trees marked by BLM in 1962 found and measured to center of trees at root crown:

- Douglas Fir, now a 10 ins. diam. snag with scribing visible in partially healed single blaze, bears N79½°E, 37.6 feet. Record: N80°E, 37.62 feet.
- Douglas Fir, now an 11 ins. diam. snag with scribing visible in partially healed single blaze, bears S37¼°W, 50.1 feet. Record: S36°W, 50.16 feet.

Scribe new trees "CS" "BT" and measure to center of tree at lower blaze:

- Douglas Fir, 11 ins. diam., bears S½°W, 28.00 feet.
- Cedar, 16 ins. diam., bears N64¼°W, 41.80 feet.

Corner lies at top of cut bank on South side dirt road, course S50°W.

September 30, 1987  
D. Edwards, Tech.  
T. Newcomb, Tech.

Edward McGinty  
County Surveyor

P. -364

V = 19¼°

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 540500

Quarter corner common to Sections 11 and 14, Township 36 South, Range 3 East, W.M.

Found at the corner position, exposed 10 ins. at top of cut-slope, the 2½ ins. diam. galvanized iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1962, marked:

T36S R3E  
S11  
¼S —  
S14  
1962

Bearing trees recorded by the BLM in 1962, found and measured to center of trees at base:

- Fir, dead, down and rotted bears Record: N80°E, 37.6 feet to center of stump hole.
- Fir snag, with partially healed single blaze revealing scribe marks "E S14 BT" bears Record: S36°W, 50.2 feet.

Bearing trees recorded on First Re-establishment in 1987, found with healed double blazes and measured to center of trees at lower blaze:

- Douglas Fir, now 16 ins. diam. bears Record: S½°W, 28.0 feet.
- Cedar, now 20 ins. diam. bears Record: N6¼°W, 41.8 feet.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Douglas Fir 9 ins. diam. bears N70°E, 10.7 feet.
- Douglas Fir 7 ins. diam. bears S71°E, 8.9 feet.

Corner lies westerly approximately ½ mile along gated dirt road.

November 1, 2007

H. Durkee  
B. Beeman

Roger R. Roberts  
Jackson County Surveyor

P. - 239  
V. - 16°35'