

FIRST RE-ESTABLISHMENT

GCDB 600240

Quarter corner common to Sections 25 and 26, Township 36 South, Range 3 East, W.M.

Found 2½ ins. diam. galvanized iron pipe with 3½ ins. diam. brass cap set by the BLM in 1966 tipped northwesterly approximately 1 feet. Straightened said monument, exposed 10 ins., and re-built mound of stones. Cap is marked:

T36S R3E
¼
S26 | S25
1966

Single remaining original bearing tree recorded by R. Moore of the GLO in 1883, a Yellow Pine now 36 ins. diam. with opened and re-healed face, bears Record: S70°E, 35.6 feet to face.

Bearing trees recorded by the BLM in 1966 found with healed single blazes and measured to center of trees at lower blaze:

- Douglas Fir, now 19 ins. diam. bears N35°E, 11.2 feet. Record: N39°E, 10.6 feet.
- Douglas Fir high-stump bears west 25.6 feet. Record: 25.1 feet.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Douglas Fir 14 ins. diam. bears N12½°W, 8.8 feet.
- No trees of size in southwest quadrant.

Corner lies approximately 40 feet west of blocked dirt road.

May 23, 2007

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 126
V. - 15°40'