

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 1 ONLY
GCDB 700640**

Quarter corner to Section 1 only, Township 36 South, Range 3 East, W.M. $V = 17^\circ$

Found, firmly set, the original 8 x 10 x 12 ins. stone, recorded as 16 x 10 x 6 ins. by R. Moore in 1883.

Said stone found marked "S1¼" on West face as reported on 1925 retracement by L. Wilkes. Bearing trees recorded by Wilkes found as follows:

- Douglas Fir, 32 ins. diam. with healed blazes, bears Record: $S64\frac{1}{2}^\circ W$, 29.70 feet to center.
- Sawed Fir stump, 37 ins. diam., bears record $N36\frac{3}{4}^\circ$, 26.40 feet to center.

I replace original stone with, and deposit it alongside, a 1 x 36 ins. G.I. pipe set 30 ins. in the ground, with a 2½ in. bronze disc marked:

JACKSON COUNTY 1978
T36S R3E
¼S 1 | R4E

And mark a new tree CS BT:

- White Fir, 7 ins. diam., bears $N58^\circ W$, 31.00 feet to center of tree at lower blaze.
- Corner lies about 185 feet West of location marker on 18 ins. diam. fir, alongside road.

November 22, 1978
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor