

FIRST RE-ESTABLISHMENT

GCDB 100240

Re-establishment of the Quarter corner on the range line between Section 30, Township 36 South, Range 4 West and Section 25, Township 36 South, Range 5 West.

Found stone 10"x10"x2" marked $\frac{1}{4}$ on West face from which the original BT a 24" Black Oak plainly scribed $\frac{1}{4}$ S S.25 BT, also remains of White Oak BT to Northeast as described in official field notes for September 12, 1905.

Also found stump of original BT to Southeast and line tree to South with 3 notches, which evidence checked very good. From the above mentioned sand stone corner a 16" White Oak scribed CS-BT bears South 12° East, 69.0 feet, the original BT bears South 58° West, 11.3 feet.

October 22, 1937

C. Z. Boyden

C. I. Bourne

C. S. Hatch - present

C. H. Lacrosse - present

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100240

Quarter corner on County Line, between Section 30, Township 36 South, Range 4 West and Section 25, Township 36 South, Range 5 West, W.M.

At the corner, found the 16 x 10 x 9 ins. stone, firmly set, 10 ins. in the ground, marked "¼" on West side, as recorded on 1905 GLO retracement, by H. Perkins.

Replace said stone with a 1 x 36 ins. galvanized iron pipe, set 30 ins. in the ground with a 2½ ins. diam. bronze cap marked:

JACKSON COUNTY 1982
T36S
R5W R4W
25 | 30
¼s

- An original bearing tree recorded by Ives and Hyde in 1854, now a rotted Black Oak stump, about 16 ins. diam., with reverse impression of axed face and chain notch, brs. S59°W, 11.3 feet to said (reverse) chain notch. Record; S58°W, 11.88 feet.
- Bearing tree marked on First re-establishment, page 9, in 1937, a partly dead White Oak, now 19 ins. diam. containing scribe marks in partially exposed upper face, brs. S12°E, 69.7 feet to center. Record; 69.0 feet.
- A Black Oak, 8 ins. with double blazes (reference tree of un-known origin, not scribed in opened upper face) brs. N38°W, 9.6 feet to center.

Deposit found stone alongside corner, mk. new trees "C.S." "BT" and take measurements to center of trees at lower blaze:

- Douglas Fir, 12 ins. diam., brs. N47½°E, 24.17 feet.
- Cedar, 18 ins. diam., brs. N27°W, 41.25 feet.

Corner lies about 40 feet West of draw C. S40°E, and approximately 500 feet Northerly of location marker on 8 ins. diam. White Oak alongside dirt road.

March 10, 1982
R. Frost
R. Templin

Edward McGinty
County Surveyor

V = 20°
P. -31