

FIRST ESTABLISHMENT

GCDB 140240

Establishment of Center quarter to Section 30, Township 36 South, Range 4 West.

Set at the intersection of the N. and S. with the E. and W. center lines, 7/8"x13" drill steel for corner in an 8" drill hole in the solid rock out-crop

From which:

- A 6" White Oak scribed CS-BT bears North $143\frac{1}{4}^{\circ}$ E., 15.7 feet;
- A $\frac{3}{4}$ "x23" iron pipe bears East 100 feet;
- Scribe a 9" Black Oak CS-BT which bears South $58\frac{1}{4}^{\circ}$ East, 56.4 feet;
- A 4" White Oak previously scribed $\frac{1}{4}$ bears South 53° West, 26.4 feet;
- Set a $\frac{3}{4}$ "x18" iron pipe which bears West, 309.0 feet.

October 25, 1937
C. Z. Boyden, Deputy County Surveyor
C. I. Bourne, Chainman
C. S. Hatch & C.H. LaCrosse, Axemen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 140240

Center Quarter corner of Section 30, Township 36 South, Range 4 West, W.M. $V = 18^\circ$

Found 1 in. diam. drill steel, projecting 5 ins. from rock outcrop. I mark the top of drill steel:

"C.S."
1979+
C $\frac{1}{4}$

References recorded in 1937 found as follows:

- Iron pipe $\frac{3}{4}$ in. diam., projecting 1 in. brs. East, 99.79 feet. Record; East, 100 feet.
- Black Oak snag, 12 ins. diam., with healed blazes, brs. $S58\frac{1}{4}^\circ E$, 56.51 feet to center of tree. Record; $S58\frac{1}{4}^\circ E$, 56.4 feet.
- White Oak, 7 ins. diam., with healed blaze, brs. $S53^\circ W$, 26.27 feet to center of tree at base. Record; $S53^\circ W$, 26.4 feet. I re-scribe this tree "CS" "BT".

I mark a new tree "CS" "BT":

- Ponderosa Pine, 18 ins. diam., brs. $N45\frac{1}{2}^\circ W$, 63.97 feet to center of tree at lower blaze.

Corner lies about 320 feet east of the center of Savage Creek Road.

November 26, 1979
J. Swanson
R. Frost

Approved by: Edward McGinty
County Surveyor