

FIRST RE-ESTABLISHMENT

GCDB 140300

Quarter corner common to Sections 19 and 30, Township 36 South, Range 4 West, W.M.

Found the corner marked with an iron pin 2" diam. from which the stump of the Yellow Pine witness tree bears S53°W., 48 lks.

Blazed and marked two trees to wit:

- An 18" Maple bears S43½°W, 118.8 feet.
- A 10" black oak bears N40°45'E, 150.9 feet.

April 30, 1913

A. T. Brown, Deputy County Surveyor

C. D. Runyon, M. B. Kellogg, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 140300

Quarter corner common to Sections 19 and 30, Township 36 South, Range 4 West.

Found 2" iron pin to mark the corner, also stump of 10" black oak to Northeast as described by County Surveyor A.T. Brown, April 30, 1913.

From said iron pin for corner,

- A 12" alder scribed CS-BT bears South $52^{\circ}30'$ East, 6.6 feet,
- The center of the pavement on the Pacific Highway bears South 49.5 feet,
- The top center of a 14"x18" concrete post, the Northeast post of Savage Creek Bridge, bears South 52° West, 88.8 feet.

October 25, 1937
C. Z. Boyden
C. I. Bourne

SEE NEXT PAGE FOR RE-ESTABLISHMENT SPECIAL CORNER

FIRST RE-ESTABLISHMENT SPECIAL CORNER
GCDB 140300

Quarter corner common to Sections 19 and 30, Township 36 South, Range 4 West, W.M.

Found a 1½ ins. galvanized iron pipe 12 ins. below the ground and found on Survey No. 3430, dated 1967, which stated that the pipe had a tag marked R.S. 404. No record can be found as of this date of a Survey by R.S. 404.

Set a 1 x 36 ins. galvanized iron pipe inside of found pipe 38 ins. in the ground with a 2½ ins. diam. brass cap marked:

T36SR4W
19
¼S —
30
CS
1990

Corner is surrounded by a piece of 8 ins. diam. concrete pipe.

References taken on Survey No. 3430 found:

- State Hwy benchmark 2½ ins. brass cap in the NE corner of wing wall of a concrete box culvert, which replaced old bridge in 1957, on Savage Creek brs., S64°04'W, 93.64 feet. Record; S70°W, 93.50 feet.
- Power Pole No. 3/22 "Old No. 6390" brs. N89°34'E, 92.91 feet. Record; N89°E, 92.80 feet.
- ¾-ins. iron pipe set on Survey No. 3430 found 3 ins. below the surface of road in shoulder brs., S89°55'E, 149.90 feet. Record; 150.00 feet.

Take new reference:

- A concrete patio and boat dock with brick trim, brs., N15°38'W, 102.20 feet to the SE corner.

Corner lies on level area of RV Park at Westerly end and approximately 50' Northerly of the center line of Hwy 99.

October 13, 1990
T. Newcomb, Tech.
S. Beecher, Tech.

Verlyn Thomas
County Surveyor

P.-134