

## SPECIAL CORNER

### FIRST RE-ESTABLISHMENT

GCDB 140400

Quarter corner common to Sections 18 and 19, Township 36 South, Range 4 West, W.M.

Found the 1½ ins. diam. galvanized iron pipe, set in 1959 on Survey No. 1327, protruding 5 ins. above the ground in a small mound of stone. To perpetuate this position, set a 5/8 x 6 ins. rebar with yellow plastic cap marked "Jackson C.S." in cement inside of found pipe.

Bearing trees marked on Survey No. 1327 found and measured to center of trees at base:

- Ponderosa Pine, 18 ins. diam. with "RS40" scribe visible on partially healed single blaze, brs. N56°W, 39.3 feet. Record; 39.6 feet.
- White Oak, 7 ins. diam. with healed double blaze brs. Record: S46¾°W, 64.0 feet.

Corner lies on 30% Southwest slope in heavy manzanita, two prominent Ponderosa Pines, one a bearing tree, near corner.

Location tag posted on 5 ins. diam. Black Oak on East side of paved single lane road approximately 100 feet South of large gravel stockpile, tag reads corner approximately 600 feet East.

July 16, 1987  
S. Beecher, Tech I  
R. Frost

Edward McGinty  
County Surveyor

V = 19°  
P. -251