

FIRST RE-ESTABLISHMENT

GCDB 140600

Quarter corner common to Sections 6 and 7, Twp. 36 South, Range 4 West, W.M. $V = 20\frac{1}{2}^\circ$

Found, iron pipe, 2 ins. diam., in mound of stone, set on survey No. 1833, dated 1961.

I set a 1x36 ins. G.I. pipe (inside found 2 ins. pipe) 24 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc. marked:

Jackson County 1975
T36S R4W
6
 $\frac{1}{4}S$ —
7

Original BTs recorded by C. J. Howard in 1883, found as follows:

- A Black Oak, 14 ins. diam., scribed " $\frac{1}{4}S$ " and "BT" in exposed faces bears record, $N49\frac{3}{4}^\circ E$, 26.4 feet to scribed lower face.
- A Black Oak snag, 18 ins. diam., scribed " $\frac{1}{4}S$ " in partially exposed upper face, bears record $S20^\circ E$, 29.04 feet to scribed upper face.

I marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- A Black Oak, 16 ins. diam., bears $N24^\circ E$, 31.82 feet.
- A Cedar, 8 ins. diam., bears $S36\frac{1}{2}^\circ E$, 43.48 feet.

Corner lies 36 feet East of stream and about 150 feet West of road.

March 25, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 140600

Quarter corner common to Sections 6 and 7, Township 36 South, Range 4 West, W.M.

Corner monument set on First Re-establishment in 1975, found bent over with cap broken off. Set in exact position of said monument, a 2½ x 30 ins. galvanized iron pipe with a 3½ ins. diam. brass exposed 6 ins. and in a mound of stones, marked:

JACKSON COUNTY SURVEYOR
T36S R4W
S6
¼ —●—
S7
2006

Original bearing trees recorded by C. J. Howard in 1883, found and re-measured to center of trees at base:

- Black Oak sawed stump with partially healed, weathered lower blaze brs. N49¾°W, 27.0 feet. Record: 26.4 feet to face of lower blaze.
- Rotted oak remains brs. S20°E, 29.8 feet. Record: 29.04 to face of upper blaze.

Bearing trees recorded on said First Re-establishment in 1975, found with double healed blazes and measured to center of trees at lower blaze:

- Black Oak, dead and down brs. Record: N24°E, 31.8 feet to center of stump hole.
- Cedar, now 12 ins. diam. brs. Record: S36½°E, 43.5 feet.
- Bearing tree of unknown origin, a Black Oak 17 ins. diam. with a 3 feet long upper blaze brs. N52½°E, 26.7 feet.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Douglas Fir 12 ins. diam. brs. S11°W, 17.9 feet.

Corner lies approximately 36 feet east of seasonal creek and approximately 200 feet west of gravel road.

March 16, 2006
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 40
V. - 17°50'