

FIRST RE-ESTABLISHMENT

GCDB 200100

Section corner common to Sections 31 and 32, Township 36 South, Range 4 West and Sections 5 and 6, Township 37 South, Range 4 West, W.M.

Found projecting 10 ins., the 24x9x7 ins. stone with notches visible in East face, reported set on Survey No. 985, in 1957.

Replaced said stone with and deposit it alongside of, a 1x36 ins. galvanized iron pipe 30 ins. in the ground. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W	
31	32

6	5
T37S	
C.S.	
1986	

From which:

- Original bearing tree marked by Ives and Hyde in 1854 found: Black Oak, now 27 ins. diam. with double rotted faces and healed blaze between, brs. Record: S13°W, 54.78 feet to estimated upper face.
- Original line tree found: Black Oak, now 34 ins. diam. with double blazes on West face, brs. S87¾°E, 68.34 feet to center of tree. Record: East, 71.28 feet.

Bearing trees marked on Survey No. 985 found and measured to center of tree at root crown:

- Yellow Pine, now 27 ins. diam. with single healed blaze, brs. N5¼°E, 41.78 feet. Record: 6°E.
- Black Oak, now 13 ins. diam. with single healed blaze, brs. S44¾°E, 32.42 feet. Record: S47°E, 32.7 feet.
- Yellow Pine, now 19 ins. diam. with single healed blaze, brs. N42½°W, 53.26 feet. Record: N44°W, 52.8 feet.

Corner lies on a 60% West slope, in a wooded area, an estimated 400 feet West of a North-South jeep road.

December 1, 1986
D. Edwards
R. Romio

Edward McGinty
County Surveyor

V = 20°
P. 343-344