

**FIRST RE-ESTABLISHMENT**

**GCDB 240100**

Quarter corner common to Section 5, Twp. 37 South, Range 4 West, and Section 32, Twp. 36 South, Range 4 West, W.M.  $V = 18\frac{1}{2}^\circ$

From the following original evidence, at the location described below, I set a 1x36 ins. G.I. pipe, 33 ins. in the ground with a 2½ ins. bronze disc marked:

JACKSON COUNTY 1979  
T36S R4W  
32  
¼S —  
5  
T37S

Original bearing trees recorded by Ives and Hyde in 1854 found as follows:

- Douglas Fir, 25 ins. diam., with axed into and rehealed upper blaze, brs. N30°E, 15.18 feet to estimated face. Re-measured 15.51 feet to center of tree. Record; N25°E, 15.18 feet.
- Laurel, 24 ins. diam., containing scribe marks in partially axed out upper face, brs. Record: S69°W, 35.64 feet to scribed face.

I mk. new trees CS BT and take measurements to center of trees at lower blaze:

- Cedar, 7 ins. diam. brs. S70°W, 13.62 feet.
- Douglas Fir, 9 ins. diam., brs. N25°W, 15.29 feet.

Corner lies on top of ridge course Northwest, about 660 feet West of location marker on 14 ins. diam. Fir located at top of cut bank alongside logging road.

March 13, 1979

B. Malotte

R. Frost

Approved by: Edward McGinty

County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT  
GCDB 240100**

Quarter corner common to Section 32, Township 36 South and Section 5, Township 37 South, Range 4 West, W.M.

Found at the corner position, exposed 3 ins., the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1<sup>st</sup> Re-establishment in 1979, marked:

JACKSON COUNTY 1979  
T36S R4W  
32  
¼S—  
5  
T37S

Original bearing trees recorded by Ives and Hyde of the GLO in 1854, found and measured to center at base:

- Sawed Fir stump 30 ins. diam. brs. N30°E, 16.0 ft. Record; N25 E, 15.2 ft. to face.
- Madrone, now 26 ins. diam. with partially healed blazes, brs. S69°W, 36.1 ft. Record; 35.6 ft. to face.

Bearing trees recorded said in said 1<sup>st</sup> Re-establishment, found with healed double blazes and measured to center at lower blaze:

- Cedar, now 11 ins. diam. brs. record; S70°W, 13.6 ft.
- D. Fir, now 13 ins. diam. brs. record; N25°W, 15.3 ft.

Mark new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Cedar 5 ins. diam. brs. S66½°E, 20.0 ft.
- No trees available in northeast quadrant due to clear-cut.

Corner is located approx. 700 ft. west of gated logging road.

February 7, 2012  
H. Durkee

Kerry Bradshaw  
Jackson County Surveyor

P. – 130  
V. – 14°