

FIRST RE-ESTABLISHMENT

GCDB 240700

Quarter corner common to Section 32, Township 35 South, Range 4 West and Section 5, Township 36 South, Range 4 West.

Found 1½" iron pipe, exposed 3", set by registered engineer J.R. White in 1947, From which:

- Original, now 20", White Oak badly decayed and no scribe bears South 63° West, 37.9 feet to the center of tree.
- Also found stump hole of original pine to Northwest.

Scribe new trees as follows:

- A 6" Black Oak, scribed "CS-BT" bears North 79¼° East, 29.0 feet to the face of the upper blaze.
- A 10" White Oak with a single blaze and brass washer with White's initials and registration number bears North 31° East, 19.1 feet. This tree not scribed.
- A 12" Pine, scribed "CS-BT" bears North 66¼° West, 18.7 feet to the face of the upper blaze.
- An 8" Laurel, scribed "CS-BT" bears South 18½° West, 22.3 feet to the face of the upper blaze.

Section corner common to Sections 5, 6, 31 and 32 bears West, 2664.0 feet.

February 10, 1967
F. Roberts
G. Nygren

Approved By:
L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 240700

Quarter corner common to Section 32, Township 35 South, Range 4 West and Section 5, Township 36 South, Range 4 West, W.M.

At the corner, found projecting 3 ins., the 1½ ins. diam. iron pipe, reported on first re-establishment, page 19, in 1967. Set a 2½ ins. diam. brass cap marked:

T35S R4W
32
¼S —
5
T36S
C.S.
1986

in the top of found pipe.

Original bearing tree recorded by S. Truax, in 1857, found:

- Black Oak 21 ins. diam. with axed out faces, brs. Record S62°30'W, 36.96 feet to estimated face. Re-measured 37.9 feet to center of tree.
- Stump hole brs. Record, N3°30'W, 33.0 feet.

Reference tree, reported marked by J.R. White in 1947, found:

- White Oak, 11 ins. diam. with a single healed blaze, brs. N30°37'E, 19.50 feet. Record (1967) N31°E, 19.1 feet.

Bearing trees marked on first re-establishment found and measured to center of tree at lower blaze:

- Black Oak 7 ins. diam. with healed blazes, brs. N78°27'E, 29.15 feet. Record: N79¼°E, 29.0 feet.
- Ponderosa Pine 11 ins. diam. with partly healed blazed, brs. N66°15'W, 19.05 feet. Record: 18.7 feet.
- Madrone 10 ins. diam. with healed blazes, brs. S19°11'W, 22.62 feet. Record: S18½°W, 22.3 feet.

Found ⅝ ins. rebar with a yellow plastic cap marked RE 5685 set on Survey No. 6067, brs. N89°56'30'E, 10.0 feet. Corner lies on level area about 250 feet north of wood frame house.

March 21, 1986
D. Edwards
T. Newcomb

Edward A. McGinty
County Surveyor

P.-61