

FIRST RE-ESTABLISHMENT

GCDB 300140

Quarter corner common to Section 32 and 33, Twp. 36 South, Range 4 West, W.M. $V = 19^\circ$

From the following evidence, at the location described below, I set a 1x36 ins. G.I. pipe, 28 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1977
T36S R4W
¼S
32 | 33

Original BTs recorded by C. Howard in 1883, found as follows:

- Black oak, 22 ins. diam., scribed "¼" in partly exposed face, bears record, $S79^\circ E$, 33.00 feet to scribed face.
- Black oak, 42 ins. diam., with healed blazes, bears record, $N65\frac{1}{2}^\circ W$, 50.82 feet to estimated face.

I marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- Douglas fir, 8 ins. diam., bears $S41\frac{1}{2}^\circ E$, 18.14 feet.
- Black oak, 11 ins. diam., bears $S84^\circ W$, 55.36 feet.

Corner lies at the base (south side) of an 8 ins. diam., douglas fir, located an estimated 65 feet South of ridge top and about 275 feet East of location marker on 6 ins. diam., ponderosa pine alongside new road.

February 1, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor