

FIRST RE-ESTABLISHMENT

GCDB 300200

Section corner common to Section 28, 29, 32 and 33, Twp. 36 South, Range 4 West, W.m.
V = 19½°

Found, the single remaining original BT recorded by C. J. Howard in 1883, now a down and rotted black oak, about 12 ins. diam., containing reverse impression of scribed "ST", the rotted stump of which, about 19 ins. diam., contains reverse impression of scribed (partial) "B" and "T" and axed chain notch.

From the preceding evidence:

- I set a 1x36 ins. G.I. pipe 28 ins. in the ground with a 2½ ins. bronze disc. marked:

Jackson County 1977	
T36S R4W	
29	28

32	33

From which:

- The above-described stump bears record, N11½°W, 61.38 feet to (reverse) chain notch.

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- Douglas fir, 18 ins. diam., bears N2°E, 94.44 feet.
- Douglas fir, 5 ins. diam., bears S89½°E, 13.20 feet.
- Douglas fir, 13 ins. diam., bears S14½°W, 121.15 feet.
- Douglas fir, 5 ins. diam., bears N29°W, 35.83 feet

Corner lies in old landing.

February 1, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor