

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 300440

Quarter corner common to Sections 16 and 17, Township 36 South, Range 4 West, W.M.

Found the 1½ x36 ins. iron pipe set on Survey No. 1834, dated 1961 by proportionate method, protruding 11 ins. above a large mound of stone.

Set a yellow plastic cap, marked Jackson C.S., in cement, in the top of found pipe.

Bearing trees marked on Survey No. 1834 found:

- White Oak, 8 ins. diam. with healed single blaze brs. S35½°E, 30.3 feet to center of tree at base. Record 29.7 feet.
- Douglas Fir stump, 20 ins. diam. with scribed "04 BT" visible brs. N4½°W, 18.3 feet to center of tree at base. Record; N3°W, 18.5 feet.

To perpetuate this position, marked a new tree "CS" "BT" and measure to center of tree at base:

- Black Oak 8 ins. diam., brs. N59°W, 49.3 feet.

Corner lies on rocky flat, approximately 200 feet North of J. H. Baxter location tag on 5 ins. diam. Oak on North side of dirt road off power line access road and northwest of large borrow pit.

August 5, 1987
S. Beecher, Tech I
R. Frost, Tech III

Edward McGinty
County Surveyor

V = 17¼°
P. -281