

## FIRST RE-ESTABLISHMENT

GCDB 340300

Quarter corner common to Sections 21 and 28, Township 36 South, Range 4 West, W.M.

Found projecting 6 ins., the 1 ins. diam. galvanized iron pipe, set on Survey No. 5607 dated 1974. In the top of found pipe, in cement, set a 2½ ins. diam. brass cap marked:

	T36S
	R4W
	<u>21</u>
¼S	28
	C.S.
	1987

The single remaining original bearing tree recorded by Ives and Hyde in 1854,

- Now an oak snag, 20 ins. diam. containing reverse impression of scribed "T" and chain notch in opened lower face, brs. S34°E, 44.88 feet to said "notch". Record; S33°E.

Bearing trees marked on the above noted survey, found and measured to center of trees near base:

- Douglas Fir, 18 ins. diam., with H3B, brs. Record: S6½°E, 42.89 feet.
- Douglas Fir, 19 ins. diam., with H3B, brs. Record: N35°W, 21.21 feet.

Corner lies on Easterly (50%) slope, about 100 feet Easterly of aluminum tag marked "¼ 100'" on 18 ins. diam. pine, located atop ridge c. northerly.

July 21, 1987  
R. Frost, Tech.  
S. Beecher, Tech.

Edward McGinty  
County Surveyor

V-18½°

P. -261