

FIRST RE-ESTABLISHMENT

GCDB 340340

Center quarter corner to Section 21, Township 36 South, Range 4 West, W.M.

Found 8 ins. deep, the 2 ins. diam. iron pipe, set on Survey No. 5607, dated 1974. To perpetuate this location, in the top of found pipe, set a 2½ ins. diam. brass cap, marked:

T36S R4W
C¼ + S21
C.S.
1988

Bearing trees marked on the above noted survey found with healed single blaze(s) and measurements taken to center of tree(s) at lower blaze:

- Douglas Fir, 20 ins. diam., brs. S58°52'E, 68.64 feet. Record: S58°45'E, 68.31 feet.
- Douglas Fir, 24 ins. diam., brs. N21°03'W, 37.79 feet. Record: N21°15'W, 33.24 feet.
- A 1½ ins. diam. pipe, found projecting 10 ins., 3 feet South of shoulder of cut-bank, brs. S2°43'W, 17.02 feet. Record: S2°58'20"W17.14 feet. **Note:** This pipe was set for center of section in 1911 as recorded on Riverdale Tracts Subdivision.

Corner lies 1.5 feet North of middle of dirt road c. East-West and about 75 feet West of draw c. N45°W near fork in roads c. North and N20°E.

- A 2 ins. diam. pipe, found 3 ins. deep, commonly accepted as the monument set in 1911, marking the most southerly corner of Lot 5, RIVERDALE TRACTS SUBDIVISION brs. N0°17'13"W, 363.24 feet.

To perpetuate the position of this pipe, located on West (48%) slope about 22 feet south of ridge c. N45°W, mark the following trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Madrone, 10 ins. diam., brs. N59½°E, 12.15 feet.
- Madrone, 7 ins. diam., brs. S82°W, 1.75 feet.

The top of a 1 ins. diam. galvanized iron pipe, found projecting 3 ins. and leaning Northwest brs. S6½°E, 27.30 feet. No record of this pipe has been found

SEE ALSO SURVEY NO. 11200.

May 12, 1988
R. Frost, Tech.
S. Beecher, Tech.

Edward McGinty
County Surveyor

P. -226