

FIRST RE-ESTABLISHMENT

GCDB 340600

Quarter corner between Sections 4 and 9, Township 36 South, Range 4 West, W.M.

Found the stump of a 30" yellow pine tree with old blaze visible. No evidence of the original bearing tree to the northeast.

Set a 1"x36" galvanized iron pipe 36" in the ground for corner at the official record course and distance from the above mentioned stump, from which the following bearing trees were set off and scribed CS-BT:

- A 12" red fir bears N15°00'E, 72.1 feet.
- A 5" white oak bears S68°00'W, 80.8 feet.

Mr. D. P. Magerle certifies that the above mentioned stump is the recognized original bearing tree and that he has seen the scribe thereon.

November 23, 1936
C. Z. Boyden, Deputy County Surveyor
C. Bourne
D. Clifford
D. P. Magerle, Witness

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 340600

Quarter corner common to Sections 4 and 9, Township 36 South, Range 4 West.

Found the 1" galvanized iron pipe and the bearing tree to the Northeast as established by Deputy County Surveyor C. Z. Boyden on November 23, 1936.

The established bearing tree to the Southwest has been destroyed.

From said pipe corner I establish a new witness tree as follows:

- A 14" Yellow Pine scribed "CS-BT" bears South $34\frac{3}{4}^{\circ}$ East, 46.8 feet.

October 1960
F. Roberts
O. Blankenship

Approved By:
Mark E. Boyden,
Deputy County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 340600

One-quarter corner common to Sections 4 and 9, Township 36 South, Range 4 West, W.M.

Found at the corner the 1 ins. G.I. pipe, flush, as described in the Second re-establishment, 1960, page 19, and witnessed by:

- A sawn Fir stump, 14 ins. diam. brs. record (First re-establishment) N15°E, 72.1 feet to center.
- A 5/8 ins. rebar on the Easterly right-of-way line of West Evens Creek Rd. per recorded Survey No. 5499, brs. N89°53'43"E, 1253.22 feet. Record: 1253.24, basis of bearing.

No other evidence of original bearing trees or other trees marked on First or Second re-establishment.

I scribe new trees "CS-BT" and measure to the center of:

- A 15 ins. Ponderosa Pine, brs. N3°44'W, 17.8 feet.
- A 9 ins. Ponderosa Pine, brs. S22°26'E, 68.7 feet.

Corner lies at new East fence; old North-South fence intersection next to 4x6 ins. wood post.

October 7, 1980
J. Swanson
Witness: J. Wentling
K. Martin, PW Dept.
N. Misek, PW Dept.

Edward McGinty
County Surveyor

P. 199-200

NOTE: 10/30/1995

Set brass cap in found 1 in. pipe marked:

T36SR4
W
¼S ——— 4 ——— C.S.
9
1995

R. Frost
T. Newcomb