

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 36 South, Range 4 West, W.M.

At the corner, found projecting 8 ins. from a mound of stone, the 1½ ins. diam. iron pipe set for the corner on Survey No. 2047 in 1960.

In top of said pipe set in cement a 2½ ins. diam. brass cap marked:

T36S R4W

28	27
33	34
C.S. 1982	

Bearing trees marked on above noted survey found:

- Sugar Pine, 39 ins. diam. containing scribe marks in partially exposed single face, brs. N57°E, 29.4 feet to center. Record: 29.7 feet.
- Black Oak, 13 ins. diam., with healed single blaze, brs. S73°W, 35.42 feet to center. Record: 34.32 feet.
- Ponderosa Pine, 23 ins. diam., containing scribe marks in partially healed single face, brs. N29°W, 25.55 feet to center. Record: 25.74 feet.

Original bearing trees marked by Ives & Hyde in 1854 and noted in 1960 found as follows:

- Black Oak, 14 ins. diam., with axed into faces, brs. N75°E, 12.0 feet to center. Record (1960) N73°E, 12.54 feet.
- Black Oak, 22 ins. diam., with healed blazes, brs. S11°E, 16.15 feet. Record: (1960) 15.84 feet.
- The core of a rotted pine, about 5 feet high, brs. S18°W, 52.23 feet to center. Record: 51.48 feet.
- Hollow Black Oak, partial shell supporting new growth, 19 ins. diam., brs. N51°W, 44.02 feet. Record: (1960) 44.88 feet.

Corner lies on West (55%) slope, about 300 feet West of ridge top and 65 feet North of the head of draw C. West. The top center of roof of hexagon shaped house brs. N79°W and estimated 1500 feet distant.

June 22, 1982
E. McGinty
R. Frost

Edward McGinty
County Surveyor

V = 18½°

P. -89

ALSO SEE RECORDED SURVEY NO. 2955