

FIRST RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 36 South, Range 4 West, W.M.

Found 15 ins. deep, the 1 ins. diam. iron pipe set by proportionate method for corner on Survey No. 5607, dated 1974. References noted on said survey found:

- Apple tree, 15 ins. diam., brs. S15°14'E, 50.0 feet to center. Record; S15°30'E.
- Apple tree, 14 ins. diam., brs. S11°46'W, 63.49 feet to center. Record; S12°W, 63.4 feet.

To perpetuate this location, in the top of found pipe, set a 2½ ins. diam. brass cap, in cement, marked: "C.S. 1982" and take new references:

- Reba 5/8 x3 0 ins., set 28 ins. in the ground on fence line c. N65°E, with yellow plastic cap marked "Jackson C.S.", brs. N2°56'51"E, 136.00 feet.
- Iron pin ½ ins. diam., found 2 ins. deep, located approximately 12 feet North of the center of Lost
- Lane road and about 57 feet S60°W of power pole No. R4491, brs. S2°56'51"W, 151.67 feet.
- Iron pin 5/8 ins. diam. found projecting 3 ins., at the northerly end of cyclone fence, c. S30°E and about 1 feet south of fence line c. N65°E, brs. S54°10'W, 26.52 feet.
- Iron pipe 1 ins. diam. apparently old and of unknown origin, found 2 ins. deep, about 9 feet north of fence line, c. N65°E, S64°20'W, 178.07 feet.

Corner lies 436.97 feet N0°17'54"E of the (brass cap) Ell corner of DLC 39.

August 25, 1982
E. McGinty
R. Frost
R. Templin

Edward McGinty
County Surveyor

P. 125-126