

FIRST RE-ESTABLISHMENT

GCDB 400400

Section corner to 15, 16, 21, 22, Township 36 South, Range 4 West, W.M.

Find corner marked by stone with cross from which one original W.T. a B.O. bears $N61^{\circ}W$, 42.2 feet. Cut cross in Northeast corner of cement foundation of Woodville City Hall and cross in Southeast corner of same. The former bears 26.48 feet from corner and the latter 35.95 feet from corner.

Note: the stone has been replaced by a 1" gas pipe set in concrete.

March 24, 1913
A. T. Brown, Deputy County Surveyor
C. D. Runyon, M. B. Kellogg, Chainmen

NOTE: March, 1962

Found NE corner of above foundation 27.95 feet.
L.D.P.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400400

Corner common to Sections 15, 16, 21 and 22, Township 36 South, Range 4 West.

Found a $\frac{3}{4}$ " pipe in concrete in monument case 9" below the surface of the road. It has been known for many years that this is the same monument which is reported as a 1" pipe in the re-establishment records. Recent construction of a service station has destroyed the old references.

The following new references were taken:

- A cross in the Southeast corner of a concrete slab around the pump island of a "Gulf" service station bears North $39^{\circ}09'$ West, 62.48 feet;
- A cross, 1.7 feet from the Southeasterly end of a concrete curb, bears South $49^{\circ}13'$ West, 48.55 feet;
- A cross on the Westerly side of the concrete base of a light pole bears North $87^{\circ}52'$ East, 31.01 feet.

August 21, 1967
F. A. Roberts
J. Huston

Approved by:
L. D. Pinkham
Deputy County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400400

Section corner common to Sections 15, 16, 21 and 22, Township 36 South
Range 4 West, W.M.

Found 10 ins. deep, $\frac{3}{4}$ ins. diam. iron pipe in concrete, reported on Second Re-establishment, page 22, in 1967. Directly over found pipe, flush with the surface of street, set a $2\frac{1}{2}$ ins. diam. brass cap in concrete, marked:

T36S R4W	
16	15
21	22
C.S.	
1987	

References set in 1967 found:

- Tack in lead, atop concrete curb, located 1.6 feet Northwest of the Southeast end, brs. $S49^{\circ}14'W$, 48.55 feet. Record; "cross", $S49^{\circ}13'W$.
- Chiseled cross, found near the (projected) southeast corner of concrete (service station) slab, brs. $N39^{\circ}07'W$, 62.48 feet. Record; $N39^{\circ}09'W$.

Reference reported on Survey No. 1473 in 1960 found:

- The Southwest corner of concrete block (garage) building, brs. $N78^{\circ}36'E$, 67.17 feet. Record; $N78^{\circ}E$, 67.15 feet.

Iron pipes, $\frac{3}{4}$ ins. diam., one of which was reported set on Survey No. 3264 in 1966, found 7 ins. below the asphalt surface of parking area brs:

- $S89^{\circ}27'W$, 25.95 feet.
- $S89^{\circ}17'W$, 25.99 feet.

Above pipes also reported on Survey No. 6044, dated 1975.

- A $\frac{5}{8}$ ins. diam. iron pin, with yellow plastic cap, found 3 ins. deep, being the P.I. of Pine and West Main Streets., brs. $N0^{\circ}26'10"W$, 232.94 feet.

Take a new reference:

- P-K nail in the center of and near the North end of a 6x26 feet concrete (service station) slab, brs. $S41^{\circ}03'E$, 64.58 feet.

January 6, 1987
R. Frost
T. Newcomb
R. Romio

Edward A. McGinty
County Surveyor

P. 1-2

FOURTH RE-ESTABLISHMENT

GCDB 400400

Section corner common to Sections 15, 16, 21 and 22, Township 36 South
Range 4 West, W.M.

Found 3 ins. deep in a monument case the 2½ ins. diam. brass cap set on the Third Re-establishment dated 1987 marked:

T36S R4W	
16	15

21	22
CS	
1987	

References reported on the Third Re-establishment found:

- The Southwest corner of concrete block (garage) building, brs. N78°36'50"E, 67.17 feet. Third re-establishment record bearing; N78°36'E.
- A ⅝ ins. diam. iron pin, with broken yellow plastic cap, found 3 ins. deep, being the P.I. of Pine and West Main Streets, brs. record N0°26'10"W, 232.94 feet.

Take new references:

- P-K nail set at the North end of island curbing brs. S26°46'48"E, 98.75 feet Island is located in front of auto repair garage.
- Chiseled 'x' with center punch mark on the East side of a 3 feet diam. x 2.5 feet high concrete lamp post base brs. S49°40'36"W, 47.35 feet Lamp post is located at the South end of gas station parking lot.

Corner lies 5 feet East of the centerline of Pine St. near end of curve.

July 29, 2007
S. Beecher
S. Fein

Roger Roberts
County Surveyor

P.4
Series II Book I