

**FIRST RE-ESTABLISHMENT**

**GCDB 400500**

Section corner to Sections 9, 10, 15, 16, Township 36 South, Range 4 West, W.M.

Found stake from which the remains of two old witness tree stumps were in proper relation.

Drove gas pipe from which a gas pipe in center of county road bears  $S89^{\circ}44'W$ , 298.4 feet.

April 26, 1913  
A T Brown, Deputy County Surveyor  
C.D. Runyon, M.B. Kellogg, Chainmen

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 400500

Section corner common to Sections 9, 10, 15 and 16, Township 36 South, Range 4 West.

Found ½" x 24" pipe in County Road (see reestablishment by A.T. BROWN, County Surveyor, April 26, 1913), from which evidence found remains of old corner post. The pipe set to mark the corner was destroyed while constructing an irrigation ditch.

Set a 2" x 36" galvanized iron pipe for corner from which the following reference points were set off:

- A ½" x 24" pipe set by Brown in the center of the County Road bears S89°44'W, 298.4 feet, as per Surveyor Brown's reestablishment record.
- The center of an irrigation ditch bears South, 7.5 feet.
- A 12" White Oak scribed CS-BT bears N 62°00' E, 196.1 feet.
- A 36" Black Oak (located in the County road) bears N55°00'W, 277.0 feet.

November 23, 1936  
C. Z. Boyden, Deputy County Surveyor  
C. Bourne  
D. Clifford

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

## THIRD RE-ESTABLISHMENT

### GCDB 400500

Section corner common to Sections 9, 10, 15 and 16, Township 36 South, Range 4 West, W.M.

Found 22 ins. deep, a 2½ ins. diam. center punched brass cap in concrete. This brass cap is described on Lloyelen Acres Subdivision, as being set in a found 2 ins. diam. galvanized iron pipe (in concrete), for subject corner and the initial point of the above noted subdivision. The 2 ins. diam. pipe found is that pipe recorded set on second re-establishment, page 8, in 1936.

Remaining references reported in 1936, found as follows:

- A ½ ins. diam. iron pipe, found 5 ins. below the asphalt surface of West Evans Creek Road, with top bent southerly, brs. S89°41'59"W, 298.37 feet to (straightened) pipe top. Record; S89°44'W, 298.4 feet.
- Black Oak, now 53 ins. diam., brs. N55°07'45"W, 278.15 feet to center. Record; N55°W, 277.0 feet **Note:** This tree not recorded to be scribed.

Additional references taken:

- A found ⅝-ins. iron pin, set on Survey No. 5638 dated 1974 and noted to be on the "section line", brs. S89°51'40"W, 330.04 feet. Record; 330.07 feet.
- A ⅝ ins. diam. iron pin, found 2 ins. deep, set on Survey No. 9600, dated 1983, brs. N89°59'19"W, 265.76 feet. Record; N89°56' 31"W, 265.86 feet.
- Set ⅝ x 18 ins. rebar with yellow plastic cap marked "Jackson C.S." flush, 1 feet north of east-west fence line brs. N88°49'E, 14.22 feet.
- Mk chiseled cross in the Southeast corner of concrete slab, brs. N28°43'18"W, 31.65 feet.

Corner lies about 1 feet West of the metal post corner of South & East bearing fence line and 18 ins. Southeast of power pole.

(No date given)  
R. Frost, Tech III  
S. Beecher, Tech I

Edward McGinty  
County Surveyor

P. 241-243