

FIRST RE-ESTABLISHMENT

GCDB 440400

Quarter corner common to Sections 15 and 22, Township 36 South, Range 4 West.

Found iron pin center County Road from which a 30" Black stump with BT scribed plainly, bears North 58° East, 44 lks.

Set 2" pipe ½ foot below surface of ground, which bears North 0°40' West, 20.0 feet, also scribed a 5" laurel bearing North 64°00' East, 77.1 feet.

March 21, 1925
C. Z. Boyden, Deputy County Surveyor
H. A. Wheeler, Chainman
M. A Stevens, present.

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 440400

Quarter corner between Sections 15 and 22, Township 36 South, Range 4 West.

Found th $\frac{1}{2}$ " x $1\frac{3}{4}$ " x ? iron pin for corner. Also a 2" x ? iron pipe North 20.0 feet, which pipe is now under cattle guard at entrance to cemetery and about 1 foot below the average ground level.

The Southwest corner of the concrete base of the Moor Tombstone bears North 43° West, 55.55 feet.

The center of a 20" Yellow Pine bears North 44° West, 29.0 feet.

July 15, 1948
C. Z. Boyden
L. D. Pinkham
G. L. Ray

ALSO SEE RECORDED SURVEY NO. 1473

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 440400

Quarter corner to Sections 15 and 22, Township 36 South, Range 4 West.

Found the ½" x 1½" iron pin for corner but the references have been disturbed or destroyed. The Moore family tombstone has been moved to allow for the construction of a concrete curb around the lot.

- The Southwest corner of the concrete base now bears North 39°34' East, 56.95 feet, (the bearing previously reported Northwest should have been Northeast).
- The Southwest corner of a 10 foot by 10 foot concrete curb around the Earl F. Pollock plat, bears North 44° 03' West, 121.10 feet.

March 31, 1967
L. D. Pinkham, Deputy County Surveyor
Gary Kaiser

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

GCDB 440400

Quarter corner common to Sections 15 and 22, Township 36 South, Range 4 West, W.M.

- On July 7, 1967, prior to road construction, found the $\frac{1}{2}$ " x $1\frac{1}{2}$ " iron pin, 6" deep as reported for corner on the Third Re-establishment by Deputy County Surveyor L. D. Pinkham on March 31, 1967.
- Also found the Southwest corner of the concrete base of the "Moore" tombstone which bears Northeasterly 56.97 feet.
- Also the Southwest corner of the concrete curb around the "Pollock" plot bears Northwesterly 121.10 feet.
- Set a $\frac{5}{8}$ " iron pin flush, being 1 foot Easterly from the Easterly granite cemetery gatepost, which bears Northeasterly 30.52 feet;
- A spike in the Southwesterly side of Power Pole #R2764 bears Southeasterly 40.18 feet.

On March 11, 1969, found all of said July 7, 1967 reference points and set a 1"x36" galvanized iron pipe with $2\frac{1}{2}$ " bronze cap for corner flush with the pavement surface, said bronze cap stamped:

T. 36 S. R. 4 W.
15
 $\frac{1}{4}$ S — Cor.
22
C.S.
1969

March 11, 1969
F.A. Roberts, Deputy County Surveyor
Gary Kaiser

SEE NEXT PAGE FOR FIFTH RE-ESTABLISHMENT

FIFTH RE-ESTABLISHMENT

GCDB 440400

Quarter corner common to Sections 15 and 22, Township 36 South, Range 4 West, W.M.

Found at the corner position, flush with asphalt, the 2½ ins. diam. brass cap set on Fourth Re-establishment in 1969, marked:

T36S R4W
15
¼S —
22
C.S.
1969

References recorded on said Fourth Re-establishment, found and re-measured:

- Southwest corner of concrete base of "Moore" tombstone brs. N 38°52'41" E, 57.32 feet. Record: 56.97 feet.
- Southwest corner of concrete curb around "Pollock" plot brs. N 58°54'14"W, 121.14 feet. Record: 121.10 feet.
- Spike in southwest side of power pole no. 2764, approximately 1.5 feet high brs. S 48°47'52" E, 40.16 feet. Record: 40.18 feet.

Take new references:

- 5/8 in. diam. rebar exposed 1 in. brs. N 14°18'08" E, 32.16 feet.
- 5/8 in. diam. rebar 0.6 feet deep brs. S 15°22'36" E, 31.00 feet.
- 2½ ins. diam. brass cap found flush and marked:

RPLS
•
No. 2339
brs. S 0°44'42" E, 29.98 feet.

Note: 5/8 in. diam. rebars found per Survey No. 6796 and used for basis of bearings.

February 5, 2008

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P.-23
Nikon Total Station